

Heat Reflecting Silicone Rubber Sealed Fiberglass Fabric
500°F / 260°C: Dual-Coat™ Aluminum Film One Side / Silicone Rubber One Side
High Temperature & Radiant Heat Reflecting with Vapor Barrier



- Heat reflecting side is aluminum film. Perfect for applications involving movement or flexing, such as for bellows construction.
- Protection from intense radiant heat up to 3000°F.
- Reflects more than 95% of the radiant heat that contacts its surface.
- Silicone Rubber side provides excellent vapor barrier and protection from lubricating oils, wash down, contamination, etc.

Additional Technical Data

Tensile Strength: Warp: 200 lbs/inch 35.72 kg/cm
 Fill: 200 lbs/inch 35.72 kg/cm

Tear Strength: Warp: 20 lbs 9.07 kg
 Fill: 20 lbs 9.07 kg

Burst Strength: 450 psi / 31.5 kg/cm²

Flame Resistance: Char length 1" max
 Afterglow 20 seconds max
 Flame Out 10 seconds max

Dual-Coat™ Radiant Heat Reflective Protection Fabric			
Aluminum Film One Side / Silicone Rubber One Side			
Part Number	Weight oz/yd² / g/m²	Thickness in / mm	Roll width in / mm
F-FG-ALM-SR-1750-17	17 / 578	.017 / .432	50 / 1270

- Full rolls are 50 yards / 150 feet / 45.7 metres long
- This Product is Available By-The-Yard
- Discounts for full roll purchases
- Available as a tape - custom slitting to any width is available