

Fax Orders: 610-340-9054

Telephone Orders: 610-906-3549

orders@abthermal.com

Very High Temperature & Heat Resistant Fiberglass Cloth Fabric:

Premium Grade

QA Certification

1200°F / 648°C: DeltaGlass™





- Manufactured of fiberglass yarns, has a 1200°F / 648°C continuous rating while providing high insulation value & excellent personnel protection.
- Good abrasion resistance and tensile strength.
 Filament and Texturized versions available.
- A high-performance very high temperature fabric, used in almost all industries for heat protection.
- Also available with coatings such as Vermiculite, PTFE, Aluminum foil/film, Neoprene/Latex. Also available with wire insert.

Thermal, EMI/RFI & Abrasion Protection Materials

Fax Orders: 610-340-9054 Telephone Orders: 610-906-3549 orders@abthermal.com

Very High Temperature & Heat Resistant Fiberglass Cloth Fabric: *Premium Grade* 1200°F / 648°C: DeltaGlass™

1200°F / 648°C continuous rating, high insulation value & excellent personnel protection

DeltaGlass™ Very High Temperature & Heat Resistant Plain Cloth Roll Fabric – Premium Grade			
Part Number	Weight oz/yd²	Roll Width In / cm	Thickness In / mm
F-FG-P-0760-6	6	60 / 152	.007 / .18
F-FG-P-0960-9	9	60 / 152	.009 / .23
F-FG-P-6040-24	24	40 / 101	.060 / 1.52
F-FG-P-6060-24	24	60 / 152	.060 / 1.52
F-FG-P-6540-30	30	40 / 101	.065 / 1.65
F-FG-P-6560-30 **	30	60 / 152	.065 / 1.65
F-FG-P-7540-36	36	40 / 101	.075 / 1.91
F-FG-P-7560-36	36	60 / 152	.075 / 1.91
F-FG-P-9040-40	40	40 / 101	.090 / 2.29
F-FG-P-9060-40	40	60 / 152	.090 / 2.29
F-FG-P-12540-64	64	40 / 101	.125 / 3.18
F-FG-P-12560-64 #	64	60 / 152	.125 / 3.18
F-FG-P-25060-100	100	60 / 152	.250 / 6.36

Roll length is 150 Feet / 50 yards / 45 Metres. Please call for pricing on fabric with PSA

These Products are Available By-The-Yard / Metre: Discounts for full roll purchases

^{**} Note: This fabric has MSHA-BC-109 Approval and is Marked as such.

^{*} Note: On fabrics with PSA, the PSA will burn off at temperatures above 400°F and should be used only to facilitate installation. Material with PSA should not be used in confined areas at elevated temperatures without ventilation until all of the PSA has vaporized.