

Silica/Fiberglass Blend Fabrics: *Premium Grade*
ProSil™ Plain fabric and ProSilMax™ Wire re-enforced fabric
1350°F / 723°C: Very High Temperature & Heat Resistant



- Fabric has a 1350°F / 723°C continuous rating while providing high insulation value & excellent personnel protection.
- Very good abrasion resistance and tensile strength.
- Remains soft, and pliable and conformable at temperatures where fiberglass materials become brittle.
- PROSILMAX has 1 strand of 621 Stainless Steel wire around each yarn of the fill.

1350°F / 723°C continuous rating, high insulation value & excellent personnel protection

Very High Temperature & Heat Resistant HTC Fiberglass Cloth Roll Fabric			
Part Number	Weight oz/yd²	Roll Width In / cm	Thickness In / mm
F-PROSIL-3236-18	18	36 /	.032 / 0.81
F-PROSIL-3260-18	18	60 / 152	.032 / 0.81
F-PROSIL-4560-26	26	60 / 152	.045 / 1.14
F-PROSILMAX-7060-35	35	60 / 152	.070 / 1.77

Roll length is 150 Feet / 50 yards / 45 Metres. Please call for pricing on fabric with PSA

These Products are Available By-The-Yard / Metre:

Discounts at 5, 10, 25 and 50 yard purchases