

UltraFlex™ Silicone Rubber Pipe & Hose Heating Tape
Fixed Thermostat Control
 Freeze protection and general process heating - 120 & 240 Volt



- Two temperature versions available: 70°F/21°C or 120°F/49°C.
- 6.0 watts/square inch
- Extremely flexible silicone rubber heater strip.
- Moisture and chemical resistant. IP66 rating.
- Safe for use on metal surfaces.
- Multi-strand resistance element for mechanical durability.
- Heater strip maximum exposure 450°F 232°C.
- 5 foot 1.8m power cord with 2 prong plug for 120VAC. Bare wire pigtail for 240VAC.
- Custom temperature setting and lengths available.

UltraFlex™ Pipe & Hose Heating Tapes - Fixed Thermostat			
Part Number	Size of heat tape width / length	Voltage	Watts
FAB-SR-UFTRACE-0510-X-Y	0.50" / 10 ft	120 / 240	60
FAB-SR-UFTRACE-0520-X-Y	0.50" / 20 ft	120 / 240	120
FAB-SR-UFTRACE-0540-X-Y	0.50" / 40 ft	120 / 240	240
FAB-SR-UFTRACE-0550-X-Y	0.50" / 50 ft	120 / 240	300
FAB-SR-UFTRACE-0560-X-Y	0.50" / 60 ft	120 / 240	360
FAB-SR-UFTRACE-0575-X-Y	0.50" / 75 ft	120 / 240	450
FAB-SR-UFTRACE-0580-X-Y	0.50" / 80 ft	120 / 240	480
FAB-SR-UFTRACE-05100-X-Y	0.50" / 100 ft	120 / 240	600
FAB-SR-UFTRACE-05125-X-Y	0.50" / 125 ft	120 / 240	750

For the X value, specify "120" for 120 volt or "240" for 220-240 volt operation

For the Y value, specify "70" for 70°F setting or "120" for 120°F setting

FreezeFlow™ Pipe & Hose Heating Tapes - Thermostat Controlled

Freeze protection and general process heating - 120 & 240 Volt



- Adjustable thermostat controlled heating.
- Adjustable to a maximum of 160°F / 71°C. 6.0 watts/square inch
- Extremely flexible silicone rubber heater strip.
- Moisture and chemical resistant. IP54 rating.
- Safe for use on metal surfaces.
- Multi-strand resistance element for mechanical durability.
- Heater strip maximum exposure 450°F 232°C.
- 6 foot 1.8m power cord with 2 prong plug for 120VAC. Bare wire pigtail for 240VAC.

FreezeFlow™ Pipe Heating Tapes - Thermostat Controlled			
Part Number	Size of heat tape width / length	Voltage	Watts
FAB-SR-TRACE-102-X	1" / 2 ft	120 / 240	144
FAB-SR-TRACE-104-X	1" / 4 ft	120 / 240	288
FAB-SR-TRACE-106-X	1" / 6 ft	120 / 240	432
FAB-SR-TRACE-108-X	1" / 8 ft	120 / 240	576
FAB-SR-TRACE-110-X	1" / 10 ft	120 / 240	720
FAB-SR-TRACE-115-X	1" / 15 ft	120 / 240	1080
FAB-SR-TRACE-120-X	1" / 20 ft	120 / 240	1200
FAB-SR-TRACE-130-X	1" / 30 ft	120 / 240	1440
FAB-SR-TRACE-140-X	1" / 40 ft	120 / 240	1440
FAB-SR-TRACE-150-X	1" / 50 ft	120 / 240	1440

For the X value, specify "120" for 120 volt or "240" for 220-240 volt operation