



Hook and Loop Closure – Nylon / Nomex®



Nylon hook and loop closure with Urethane/Acrylic backcoat with Flame Retardant additive. 225°F / 107°C Continuous; 300°F / 148°C for up to 1 hour; 459°F / 237°C melting point. Color is black. Nomex® is rated - 70°F to 350°F (-56°C to 176°C)

Nylon meets the following specifications:

- MIL-F-21840 / A-A-55126 Type II Class I
- NFPA 1971-1991
- Automotive FMVSS 302
- FAA 25.853a (Aviation)
- Toxicity ATS1000 (Nylon only)

| FlameShield™ Nylon Hook & Loop Flame Retardant Fastener | | | | | |
|--------------------------------------------------------------------------------------------|-----------------|--------------|--------------------|-----------------------|-----------------------|
| Part Number | Material | Width | Reel length | Price per Reel | Price per Yard |
| FAB-VHL-NY-LOOP-10-B | Nylon | 5/8" | 50 yards | \$ 47.97 | \$ 4.79 |
| FAB-VHL-NY-HOOK-10-B | Nylon | 5/8" | 50 yards | \$ 47.97 | \$ 4.79 |
| FAB-VHL-NY-LOOP-12-B | Nylon | 3/4" | 50 yards | \$ 56.88 | \$ 5.68 |
| FAB-VHL-NY-HOOK-12-B | Nylon | 3/4" | 50 yards | \$ 56.88 | \$ 5.68 |
| FAB-VHL-NY-LOOP-16-B | Nylon | 1" | 50 yards | \$ 66.33 | \$ 6.63 |
| FAB-VHL-NY-HOOK-16-B | Nylon | 1" | 50 yards | \$ 66.33 | \$ 6.63 |
| FAB-VHL-NY-LOOP-32-B | Nylon | 2" | 50 yards | \$ 126.61 | \$ 12.66 |
| FAB-VHL-NY-HOOK-32-B | Nylon | 2" | 50 yards | \$ 126.61 | \$ 12.66 |
| FlameShield™ Nomex® Hook & Loop Fastener - White Color | | | | | |
| Transportation Use - Aviation / Rail / Ground / Marine | | | | | |
| Meets FAR 25.853 / Boeing DMS1982 Rev G / AA-55126B -70°F to 350°F (-56°C to 176°C) | | | | | |
| FAB-VHL-NM-HOOK-16 | Nomex® | 1 | 50 yards | \$ 337.50 | \$ 13.50 |
| FAB-VHL-NM-LOOP-16 | Nomex® | 1 | 50 yards | \$ 466.20 | \$ 18.65 |
| FAB-VHL-NM-HOOK-32 | Nomex® | 2 | 50 yards | \$ 652.50 | \$ 26.10 |
| FAB-VHL-NM-LOOP-32 | Nomex® | 2 | 50 yards | \$ 765.00 | \$ 30.60 |