



Chemical Hose Group

**Cross Linked Polyethylene Suction & Discharge Hose - 200 PSI
High-Flexibility Version**



Designed to handle a wide range of chemicals, solvents and corrosive liquids in both pressure and suction applications.

Consult or chemical resistance chart for each application. It is advisable to test the tube material prior to initial use.

Convoluted outer cover enhances flexibility.

Standard lengths of 100' and 200'.

Cut lengths available: by-the-foot / by-the-yard

Tech Data:

Tube: Clear, cross-linked polyethylene
 Cover: Green, EPDM (convoluted)
 Safety Factor: 4:1
 Temperature: -40°F to 212°F
 Ends: Soft cuffs available on standard lengths
 Vacuum Rating: 30 in/HG
 Marking: ACID-CHEMICAL SUCTION AND DISCHARGE HOSE 200 PSI WP XLPE TUBE
 Temperature Rating: Depends on specific chemical conveyed and concentration

<p align="center">Chemical Hose Group Cross Linked Polyethylene - Suction & Discharge - 200 PSI High Flexibility Convoluted Cover</p>					
Part Number	ID Size	OD Size	Bend Radius	Weight lb/ft	Price per Foot
H-C-XLPE-16	1"	1 15/32"	2.5"	0.56	\$ 18.39
H-C-XLPE-24	1.5"	1 31/32"	3"	0.80	\$ 22.12
H-C-XLPE-32	2"	2 1/2"	4"	1.15	\$ 22.37
H-C-XLPE-40	2 1/2"	3"	5"	1.41	\$ 29.45
H-C-XLPE-48	3"	3 35/64"	6"	1.89	\$ 33.06
H-C-XLPE-64	4"	4 39/64"	8"	2.69	\$ 49.97