



**Air/Water Hose Group**

**General Service Hose Assembly - 250 PSI  
50 foot hose with crow's feet universal fittings**



A tough, heavy duty, abrasion and ozone-resistant general service hose assembled with plated universal fittings, secured with a choice of two galvanized steel bands on each end or with crimp fittings. One male fitting and one female fitting.

Principally designed for Air applications, but a good multi purpose hose for fluids including water, some petroleums, and some chemicals.

**Tech Data:**

Tube: Black, EPDM  
 Cover: Red, SBR/EPDM  
 Reinforcement: Braided polyester cord  
 Safety Factor: 3:1  
 Temperature: -20°F to 180°F  
 Marking: GENERAL SERVICE AIR AND WATER - <ID> - XXX PSI WP-LOT  
 Packaging: Shrink wrapped

<b>50 foot General Service Hose Assembly - 250 PSI</b>				
<b>Part Number</b>	<b>ID Size</b>	<b>OD Size</b>	<b>Weight lb/ft</b>	<b>Price per Foot</b>
Secured with barbed fittings and 2 band clamps at each end				
H-GS-ASSM-B-12	3/4"	1 3/16"	22	\$ 133.77
H-GS-ASSM-B-16	1"	1 3/8"	33	\$ 172.33
Secured with crimped fittings at each end				
H-GS-ASSM-C-12	3/4"	1 3/16"	22	\$ 133.77
H-GS-ASSM-C-16	1"	1 3/8"	33	\$ 172.33