



Material Handling Hose Group

Commodity Discharge Hose - up to 150 PSI



Soft wall hose with high abrasion resistance tube. Ideal for applications where discharging of abrasive media is required.

Conductive for static dissipation.

Standard lengths of 100 feet.

Available in cut lengths. By-the-foot and by-the-yard.

2 ply construction.

Tech Data:

Tube: Black, NR/SBR, abrasion resistant, static-dissipating
 Cover: Black, SBR
 Reinforcement: High tensile tire cord plies
 Safety Factor: 4:1
 Temperature: -40°F to 180°F
 Marking: WET-DRY BULK COMMODITY DISCHARGE HOSE STATIC CONDUCTIVE TUBE XXX PSI WP

Commodity Discharge Hose - Up to 150 PSI						
Part Number	ID Size	OD Size	Tube Thickness	Working Pressure	Weight lb/ft	Price per Foot
H-M-COMMDIS-32	2"	2.70"	3/16"	150	1.51	\$ 19.22
H-M-COMMDIS-40	2 1/2"	3.20"	3/16"	125	1.82	\$ 23.55
H-M-COMMDIS-48	3"	3.72"	3/16"	125	2.20	\$ 28.89
H-M-COMMDIS-64	4"	4.70"	3/16"	100	2.79	\$ 32.26
H-M-COMMDIS-72	4 1/2"	5.20"	1/4"	75	3.40	\$ 40.08
H-M-COMMDIS-80	5"	5.70"	1/4"	75	3.78	\$ 43.11
H-M-COMMDIS-96	6"	6.70"	1/4"	75	4.06	\$ 52.00

For cut lengths add +15% to pricing