

Material Handling Hose Group

Synthetic Rubber Hot Tar & Asphalt Hose - 150 PSI



Rugged hose specifically designed for the transfer of petroleum based products such as high temperature asphalt, tar, hot oils.

Suitable for suction and discharge on rail cars, tank trucks, bulk stations, storage tanks and disposing units.

Standard lengths of 100 and 200 feet.

Available in cut lengths. By-the-foot and by-the-yard.

Working pressure of 150 PSI. Vacuum rating 29 in/HG.

Tech Data:

Tube:	Black, synthetic rubber, heat and abrasion resistant
Cover:	Black, anti-static, smooth with cloth. Abrasion, weather and heat resistant
Safety Factor:	4:1
Temperature:	-20°F to 350°F (intermittent)
Marking:	HOT TAR & ASPHALT HOSE 150 PSI WP

Synthetic Rubber Hot Tar Asphalt Hose - 150 PSI					
Part Number	ID Size	OD Size	Bend Radius	Weight lb/ft	Price per Foot
H-M-TAR-32	2"	2.72"	10"	1.80	\$ 37.26
H-M-TAR-48	3"	3.78"	15"	2.94	\$ 45.77
H-M-TAR-64	4"	4.79"	20"	3.89	\$ 75.01