

## Material Handling Hose Group

### Polyurethane Lined blue PVC Hose with PVC helix - 40 PSI



Premium material handling hose with a thick smooth polyurethane tube.

Ideal for dry applications where high abrasion resistance is required.

Formulated for static dissipation.

Standard lengths of 100 feet for sizes up to 4". 20', 50' and 100' lengths for sizes 5" and 6".

High flexibility in cold temperatures.

#### Tech Data:

Tube: Clear Polyurethane liner tube  
 Cover: Blue, HMW PVC, static dissipating  
 Reinforcement: PVC helix  
 Safety Factor: 3:1  
 Temperature: -40°F to 150°F  
 Marking: URE-HD-BLUE - <ID> - LOT

Polyurethane lined blue PVC with PVC helix - 40 PSI						
Part Number	ID Size	OD Size	Working Pressure	Vacuum in/HG	Weight lb/ft	Price per Foot
H-M-PPU-PVC-32	2"	2.43	40	29	0.59	\$ 11.32
H-M-PPU-PVC-48	3"	3.70"	40	29	1.23	\$ 19.13
H-M-PPU-PVC-64	4"	4.80"	35	29	2.02	\$ 31.21
H-M-PPU-PVC-80	5"	5.80"	35	28	2.57	\$ 48.89
H-M-PPU-PVC-96	6"	6.87"	30	28	3.84	\$ 60.95

Bend Radius: 2" hose is 4". 3" hose is 6". 4" hose is 10". 5" hose is 15". 6" hose is 18"

Tube Thickness: 2" hose is 1.2mm. 3" hose is 1.8mm. 4" hose is 2.00mm. 5" hose is 2.0mm. 6" hose is 2.3mm