

Material Handling Hose Group

Polyurethane Lined PVC Hose with PVC helix - 40 PSI



Abrasion resistant suction hose for use in a variety of dry vacuum applications including sandblast recovery lines, roof rock clearing and other abrasive applications.

Polyurethane lined PVC tube with PVC right-hand helix.

The formulation of the tube includes compounds that make it permanently conductive for static dissipation.

Standard lengths are 50 and 100 feet for sizes up to 5". 20, 50 and 100 feet standard lengths for size 6". 20 and 50 feet standard length for 8" size.

Tech Data:

Construction: Polyurethane lined PVC tube with a rigid PVC right-hand helix, conductive
 Safety Factor: 3:1
 Temperature: -40°F to 150°F

Polyurethane Lined PVC Hose with PVC Helix - 40 PSI						
Part Number	ID Size	OD Size	Working Pressure	Vacuum in/HG	Weight lb/ft	Price per Foot
H-M-PU-PVC-B-32	2"	2.40"	40	29	0.51	\$ 9.16
H-M-PU-PVC-B-40	2 1/2"	3.10"	40	29	0.77	\$ 11.75
H-M-PU-PVC-B-48	3"	3.55"	40	29	0.87	\$ 14.64
H-M-PU-PVC-B-64	4"	4.68"	35	29	1.55	\$ 25.71
H-M-PU-PVC-B-80	5"	5.71"	30	28	2.30	\$ 40.04
H-M-PU-PVC-B-96	6"	7.05"	30	28	3.40	\$ 49.42
H-M-PU-PVC-B-128	8"	9.05"	30	28	4.88	\$ 82.47

Bend Radius: 2" hose is 2". 2 1/2" hose is 4". 3" hose is 5". 4" hose is 6". 5" hose is 10". 6" hose is 12". 8" hose is 15".