



Material Handling Hose Group

Polyurethane High Flexibility Vacuum Hose with PVC helix - 30 PSI



Heavy-duty abrasion resistant suction hose for use in a variety of wet and dry vacuum applications including vacuum trucks, hydro-excavators, sewer and storm drain cleaners, street sweepers.

Can handle a variety of materials such as crushed stone, sand, gravels, dry-cement, gains and slurries.

The formulation of the tube includes compounds that make it permanently conductive for static dissipation.

Standard lengths are 100 feet for sizes up to 6". 50 and 100 feet standard lengths for size 8".

Not recommended for constant contact with fuels or petroleum products.

Tech Data:

Construction: Polyurethane tube with a rigid PVC left-hand helix, conductive
 Safety Factor: 3:1
 Temperature: -40°F to 158°F
 Marking: POLYURETHANE SUCTION HOSE - <ID> - LOT

Polyurethane High Flexibility Vacuum Hose with PVC Helix - 30 PSI						
Part Number	ID Size	OD Size	Working Pressure	Vacuum in/HG	Weight lb/ft	Price per Foot
H-M-PU-PVC-VAC-32	2"	2.56"	30	29	0.74	\$ 11.40
H-M-PU-PVC-VAC-48	3"	3.59"	30	29	1.11	\$ 19.02
H-M-PU-PVC-VAC-64	4"	4.73"	30	29	1.80	\$ 29.22
H-M-PU-PVC-VAC-80	5"	5.51"	30	27	2.32	\$ 45.69
H-M-PU-PVC-VAC-96	6"	6.76"	15	27	2.86	\$ 56.61
H-M-PU-PVC-VAC-128	8"	8.87"	15	27	4.27	\$ 95.25

Bend Radius: 1 1/2" hose is 2". 2" hose is 3". 2 1/2" hose is 3". 3" hose is 4". 4" hose is 5". 5" hose is 6". 6" hose is 9". 8" hose is 15"