



Material Handling Hose Group

Polyurethane with PVC Cover Hose - up to 40 PSI



Abrasion resistant, polyurethane tube for material handling in dry applications, such as sandblast recovery lines, roof rock cleaning and other abrasive applications.

Constructed of static dissipating material that remains flexible at low temperature for ease of handling.

Sold in standard lengths only.

Standard lengths are 50 and 100 feet for sizes up to 5" ID. 20', 50' and 100' lengths for 6" size. 20' standard length for 8" size.

Tech Data:

Tube: Polyurethane, smooth
 Cover: Black, flexible PVC with black helix
 Safety Factor: 3:1
 Temperature: -40°F to 150°F

Polyurethane with PVC Cover - Material Handling Hose						
Part Number	ID Size	OD Size	Working Pressure	Vacuum in/HG	Weight lb/ft	Price per Foot
H-M-PUPVC-32	2"	2.40"	40	30	0.51	\$ 9.16
H-M-PUPVC-40	2 1/2"	3.10"	40	30	0.77	\$ 11.75
H-M-PUPVC-48	3"	3.55"	40	30	0.87	\$ 14.64
H-M-PUPVC-64	4"	4.68"	35	30	1.55	\$ 25.71
H-M-PUPVC-80	5"	5.71"	30	28	2.30	\$ 40.04
H-M-PUPVC-96	6"	7.05"	30	28	3.40	\$ 49.42
H-M-PUPVC-128	8"	9.05"	30	28	4.88	\$ 82.47