



**Material Handling Hose Group**

**Sandblast Hose - 150 PSI**



Can be used with grit, aluminum oxide, glass beads, etc., and is ideal for rugged service in shipyards and construction sites.

Conductive for static dissipation.

Standard lengths of 50 feet. 1 1/2" ID size standard length of 100 feet also available.

Working pressure of 150 PSI.

**Tech Data:**

Tube: Black, SBR/GUM, abrasion resistant, static-dissipating  
 Cover: Black, SBR, pinpricked for early failure detection  
 Reinforcement: High tensile tire cord plies  
 Safety Factor: 4:1  
 Temperature: -40°F to 190°F  
 Marking: PREMIUM GRADE SANDBLAST HOSE 150 PSI WP

<b>Sandblast Hose - 150 PSI</b>					
<b>Part Number</b>	<b>ID Size</b>	<b>OD Size</b>	<b>Weight lb/ft</b>	<b>Fabric Plies</b>	<b>Price per Foot</b>
H-M-SBLAST-08	1/2"	1 1/8"	0.40	2	\$ 7.05
H-M-SBLAST-12	3/4"	1 1/2"	0.57	4	\$ 9.45
H-M-SBLAST-16	1"	1 7/8"	0.94	4	\$ 11.40
H-M-SBLAST-20	1 1/4"	2 1/8"	1.18	4	\$ 11.85
H-M-SBLAST-24	1 1/2"	2 3/8"	1.35	4	\$ 14.10