

## Material Handling Hose Group

### SBR Vacuum Hose with PVC helix - 45 PSI



Specially compounded SBR to result in a vacuum hose for wet and dry material applications. Vacuum trucks, hydro-excavators, sewer and storm drain cleaning.

Static dissipating carbon black in the compound makes it suitable for sand, gravel, dry cement, metallic chips, grains and light abrasives.

Standard lengths are 100 feet for sizes up to 3". 50 and 100 feet standard lengths for sizes 4" to 6". 50 foot standard length for 8" size.

#### Tech Data:

Construction: SBR blended tube, static dissipating, with PVC right-hand helix  
 Safety Factor: 3:1  
 Temperature: -40°F to 158°F  
 Marking: ULTRAVAC SBR - <ID> - LOT

SBR Vacuum Hose with PVC Helix - 45 PSI						
Part Number	ID Size	OD Size	Working Pressure	Vacuum in/HG	Weight lb/ft	Price per Foot
H-M-SBR-PVC-24	1 1/2"	1.82	45	29	0.35	\$ 5.44
H-M-SBR-PVC-32	2"	2.43	40	29	0.52	\$ 8.89
H-M-SBR-PVC-40	2 1/2"	2.95	35	29	0.90	\$ 11.25
H-M-SBR-PVC-48	3"	3.50"	35	29	1.08	\$ 15.01
H-M-SBR-PVC-64	4"	4.63"	30	29	1.80	\$ 24.51
H-M-SBR-PVC-80	5"	5.76"	30	28	2.45	\$ 38.59
H-M-SBR-PVC-96	6"	6.73"	30	28	3.05	\$ 47.75
H-M-SBR-PVC-128	8"	9.04"	30	27	5.63	\$ 79.58

Bend Radius: 1 1/2" hose is 2". 2" hose is 2 1/2". 2 1/2" hose is 3". 3" hose is 4". 4" hose is 5". 5" hose is 6". 6" hose is 9". 8" hose is 15"