



**Material Handling Hose Group**

**Textile Concrete Hose - 1230 PSI / 85 BAR**



Heavy-duty hose designed to handle the abrasive applications such as plaster, grout and concrete.

Standard lengths of 100 feet.

50 foot lengths also available for 2" and 3" sizes.

Available in cut lengths. By-the-foot and by-the-yard.

Working pressure is 1230 PSI / 85 BAR. Burst pressure is 2650 PSI / 170 BAR

**Tech Data:**

Tube: Black, GUM/SBR blend, wear resistant  
 Cover: Black, SBR, cut and gouge resistant  
 Reinforcement: Multiple steel wire plies  
 Safety Factor: 2:1 (per ASME standards)  
 Temperature: -40°F to 200°F  
 Marking: CONCRETE PLACEMENT HOSE - WIRE XX" 1230 PSI (85 BAR) WP XX LBS/FT (F.W.C.) MEETS OR EXCEEDS ASME B30.27-2009

<b>Textile Concrete Hose - 1230 PSI / 85 BAR WP</b>					
<b>Part Number</b>	<b>ID Size</b>	<b>OD Size</b>	<b>Bend Radius</b>	<b>Weight lb/ft</b>	<b>Price per Foot</b>
H-M-TCON-20	1 1/4"	2.00"	8"	0.86	\$ 15.48
H-M-TCON-24	1 1/2"	2.19"	10"	0.92	\$ 17.37
H-M-TCON-32	2"	2.76"	12"	1.45	\$ 17.94
H-M-TCON-40	2 1/2"	3.34"	14"	1.71	\$ 30.51
H-M-TCON-48	3"	4.00"	15"	2.40	\$ 53.79
H-M-TCON-56	3 1/2"	4.15"	16"	3.07	\$ 76.50
H-M-TCON-64	4"	5.16"	18"	4.06	\$ 76.53
H-M-TCON-72	4 1/2"	5.59"	21"	4.22	\$ 117.99
H-M-TCON-80	5"	6.30"	24"	5.60	\$ 122.76
H-M-TCON-96	6"	7.33"	30"	6.80	\$ 158.76

**For cut lengths add +15% to pricing**