

**Petroleum Hose Group**

**Black High Flexibility Tank Truck Hose - 150 PSI**



Premium high flexibility hose for tank truck, in-plant and oilfield loading operations - strong and highly flexible hose.

Standard lengths of 100 / 200 foot coils. Also available By-the-foot or By-the-yard.

5", 6" and 8" ID hose lengths are 100 feet coils and by-the-foot or by-the-metre lengths.

**Tech Data:**

Tube: Black, Nitrile, 55% aromatics (ORS)  
 Cover: Black, Neoprene, convoluted high flexibility  
 Reinforcement: High tensile tire cord plies; helix wire  
 Working Pressure: 150 PSI Safety Factor: 4:1  
 Temperature: -40°F to 180°F Vacuum Rating: 30 in/HG  
 Ends: Soft cuffs on standard lengths  
 Marking: FLEXIBLE PETROLEUM TANK TRUCK HOSE 150PSI WP

<b>Petroleum Hose Group</b>					
<b>Black High Flexibility Tank Truck Hose - 150 PSI</b>					
<b>Part Number</b>	<b>ID Size</b>	<b>OD Size</b>	<b>Bend Radius</b>	<b>Weight lbs per foot</b>	<b>Price per foot</b>
H-P-BTANKHF150-24-X	1 1/2"	1.98"	1.5"	0.77	\$ 14.40
H-P-BTANKHF150-32-X	2"	2.47"	2"	1.02	\$ 16.11
H-P-BTANKHF150-40-X	2 1/2"	3.00"	2.5"	1.31	\$ 23.86
H-P-BTANKHF150-48-X	3"	3.50"	3"	1.60	\$ 25.09
H-P-BTANKHF150-64-X	4"	4.56"	4"	2.55	\$ 34.07
H-P-BTANKHF150-80-X	5"	5.72"	6"	3.86	\$ 53.55
H-P-BTANKHF150-96-X	6"	6.75"	8"	4.17	\$ 70.82
H-P-BTANKHF150-128-X	8"	8.81"	10"	6.02	\$ 139.60

**For cut lengths add +15% to pricing**

For the "X" value in the part number: use "C" to specify full coil  
 use "F" to specify length in feet