



**Petroleum Hose Group**  
**Tank Drop Hose - 65PSI**



High quality tank drop hose compatible with gasoline, diesel, biofuels (up to E-98) and biodiesel (B-100 meeting ASTM D-6751).

Extremely flexible even at sub-zero temperatures.

Use appropriate banding sleeves or banding coils for assembly accuracy.

Standard Lengths of 20, 60 and 100 feet.

Fabrications to be performed only by experienced personnel. Static wire must be properly embedded, grounded and tested prior to use to assure proper grounding of the hose and assembly.

**Tech Data:**

Tube and Cover: Clear, specially compounded polyurethane  
 Reinforcement: Rigid PVC helix (green) with synthetic yarn braiding  
 Temperature: -40°F to 150°F  
 Grounding: Embedded anodized copper wire  
 Marking: TDG - <ID> - LOT  
 Working Pressure: 65 PSI  
 Vacuum Rating: 29.8 in/HG

<b>Petroleum Hose Group</b>					
<b>Tank Drop Hose - 65 PSI / 29.8 inHG</b>					
<b>Part Number</b>	<b>ID Size</b>	<b>OD Size</b>	<b>Bend Radius</b>	<b>Weight</b>	<b>Price / Ft</b>
H-P-TDH-48	3"	3 3/4"	6"	1.21 lbs / ft	\$ 34.13
H-P-TDH-64	4"	4 4/5"	8"	1.72 lbs / ft	\$ 38.75