



Petroleum Hose Group

Heavy Duty Tank Drop Hose - 150 PSI



High quality tank drop hose for gasoline.

Lightweight and flexible.

Flexible even at sub-zero temperatures.

Use appropriate banding sleeves or banding coils for assembly accuracy.

Standard Lengths of 20, 60 and 100 feet.

Fabrications to be performed only by experienced personnel. Static wire must be properly embedded, grounded and tested prior to use to assure proper grounding of the hose and assembly.

Tech Data:

Tube and Cover: Black, specially compounded NBR/PVC (good for up to 40% aromatics).
 Reinforcement: Rigid PVC helix (red) with synthetic yarn braiding
 Temperature: -40°F to 150°F
 Grounding: Embedded anodized copper wire
 Marking: HEAVY DUTY TANK DROP HOSE 150 PSI W.P. - <ID> - LOT
 Working Pressure: 65 PSI
 Vacuum Rating: 29 in/HG

Petroleum Hose Group					
Heavy Duty Tank Drop Hose - 65 PSI / 29.8 inHG					
Part Number	ID Size	OD Size	Bend Radius	Weight	Price / Ft
H-P-TDHHD-150-32	2"	2.73"	6"	1.26 lbs / ft	\$ 37.15
H-P-TDHHD-150-48	3"	3.75"	7"	1.55 lbs / ft	\$ 52.03
H-P-TDHHD-150-64	4"	4.88"	9"	2.49 lbs / ft	\$ 61.90