

**Petroleum Hose Group**

**Heavy Duty Tank Drop Hose - 65PSI**



High quality tank drop hose for gasoline.

Lightweight and flexible.

Flexible even at sub-zero temperatures.

Use appropriate banding sleeves or banding coils for assembly accuracy.

Standard Lengths of 20, 60 and 100 feet.

Fabrications to be performed only by experienced personnel. Static wire must be properly embedded, grounded and tested prior to use to assure proper grounding of the hose and assembly.

**Tech Data:**

Tube and Cover: Black, specially compounded NBR/PVC (good for up to 40% aromatics).  
 Reinforcement: Rigid PVC helix (orange) with synthetic yarn braiding  
 Temperature: -40°F to 150°F  
 Grounding: Embedded anodized copper wire  
 Marking: TDHD - <ID> - LOT  
 Working Pressure: 65 PSI  
 Vacuum Rating: 29.8 in/HG

<b>Petroleum Hose Group</b>					
<b>Heavy Duty Tank Drop Hose - 65 PSI / 29.8 inHG</b>					
<b>Part Number</b>	<b>ID Size</b>	<b>OD Size</b>	<b>Bend Radius</b>	<b>Weight lbs per foot</b>	<b>Price / Ft</b>
H-P-TDHHD-32	2"	2.63"	5"	1.12	\$ 20.36
H-P-TDHHD-48	3"	3.81"	6"	1.38	\$ 24.57
H-P-TDHHD-64	4"	4.72"	8"	2.19	\$ 36.84