



Water Hose Group

Heavy Duty Soft Wall 4-ply Discharge Hose - up to 250 PSI



Similar to a lay-flat hose but with improved abrasion resistance and tensile strength.

Standard length is 100 feet.

Cut lengths available: by-the-foot / by-the-yard

Tech Data:

Tube: Black, SBR / EPDM blend
 Cover: Black, SBR / EPDM blend
 Reinforcement: High tensile tire cord plies
 Safety Factor: 3:1
 Temperature: -40°F to 180°F
 Marking: WATER DISCHARGE HOSE 2PLY XXX PSI WP

| Water Hose Group | | | | | |
|--|----------------|----------------|-------------------------|---------------------|-----------------------|
| Heavy Duty Soft Wall 4-ply Discharge Hose - Up to 250 PSI | | | | | |
| Part Number | ID Size | OD Size | Working Pressure | Weight lb/ft | Price per Foot |
| H-W-HDSW4PLY-24 | 1 1/2" | 1 58/64" | 250 | 0.56 | \$ 8.10 |
| H-W-HDSW4PLY-32 | 2" | 2 26/64" | 250 | 0.73 | \$ 9.27 |
| H-W-HDSW4PLY-40 | 2 1/2" | 2 58/64" | 250 | 0.88 | \$ 11.67 |
| H-W-HDSW4PLY-48 | 3" | 3 26/64" | 250 | 1.04 | \$ 12.42 |
| H-W-HDSW4PLY-64 | 4" | 4 27/64" | 200 | 1.41 | \$ 16.86 |
| H-W-HDSW4PLY-72 | 4 1/2" | 4 59/64" | 200 | 1.58 | \$ 27.75 |
| H-W-HDSW4PLY-80 | 5" | 5 28/64" | 200 | 1.89 | \$ 33.18 |
| H-W-HDSW4PLY-96 | 6" | 6 22/64" | 100 | 2.48 | \$ 29.28 |
| H-W-HDSW4PLY-128 | 8" | 8 23/64" | 100 | 3.39 | \$ 50.28 |
| H-W-HDSW4PLY-160 | 10" | 10 27/64" | 150 | 4.44 | \$ 70.02 |
| H-W-HDSW4PLY-192 | 12" | 12 34/64" | 150 | 5.30 | \$ 94.26 |

For cut lengths add +15% to pricing