



**Petroleum Hose Group**  
**Blender-Fracturing Hose - 400 PSI**



A rugged hose designed for blender/fracturing operations in oilfield and gas exploration applications.

The abrasion resistant cover is constructed to withstand extended exposure to harsh abrasive conditions.

Designed for the transfer of 98% water and sand mixtures, oil slurries and crude oil.

Standard 100 and 200 foot coils. Also available By-the-foot or By-the-yard.

**Tech Data:**

Tube: Black, NBR compound, fuel and oil resistant  
 Cover: Black, SBR/Nitrile blen compound  
 Reinforcement: High tensile tire cord plies  
 Working Pressure: 400 PSI  
 Safety Factor: 4:1  
 Temperature: -30°F to 180°F  
 Marking: 400PSI WP BLENDER/FRACTURING DISCHARGE HOSE

<b>Petroleum Hose Group</b>				
<b>Blender / Fracturing Hose - 400 PSI</b>				
<b>Part Number</b>	<b>ID Size</b>	<b>OD Size</b>	<b>Weight lb per foot</b>	<b>Price per foot</b>
H-P-BLENDFRAC400-64-X	4"	4.77"	3.02	\$ 47.22

**For cut lengths add +15% to pricing**

For the "X" value in the part number: use "C" to specify full coil  
 use "F" to specify length in feet