

Petroleum Hose Group

Fuel & Oil Delivery Transfer Hose - 250 PSI



Designed for the transfer and delivery of fuels, oils, kerosene, diesel and other petroleum based products for home, commercial, industrial, marine, vehicle and construction use.

It has a braided synthetic reinforcement allowing for extreme flexibility, reduced twisting and ease of handling, with good kink resistance. Good abrasion and oil resistance with a 250 PSI working pressure.

100, 125, 150 and 175 foot coils.

May be available in other cut lengths – please inquire.

Tech Data:

Tube: Black, NBR (ARPM Class A)
 Cover: Red, NBR (ARPM Class A)
 Reinforcement: 2 braided polyester cords
 Working Pressure: 250 PSI
 Safety Factor: 4:1
 Temperature: -40°F to 180°F
 Non-conductive: 1,800 megaOhm @ 1000 volts
 Marking: F.O.D. Fuel Oil Delivery Hose - (ID) - 250PSI WP (Lot #) (white lettering)

Petroleum Hose Group			
Fuel Oil Delivery Hose - 250 PSI			
Part Number	ID Size	OD Size	Weight lbs/ft
H-P-FOD-16-X	1"	1.50"	0.65
H-P-FOD-20-X	1 1/4"	1.79"	0.87
H-P-FOD-22-X	1 3/8"	1.88"	0.91
H-P-FOD-24-X	1 1/2"	2.09"	1.12

For the "X" value in the part number: use "CYYY" to specify full coil (YYY is length)
 use "FYYY" to specify length in feet