

**Petroleum Hose Group**  
**Frac Tank Hose - 150 PSI**



Heavy duty & rugged hose ideal for handling salt and fresh water, tank bottoms, crude oil, drilling muds and mild solutions of hydrochloric acids.

Convoluted cover for improved flexibility.

Not recommended for refined petroleum products.

Standard lengths of 100 foot coils and 39.4" sections. By-the-foot and by-the-metre lengths available.

**Tech Data:**

Tube: Black, custom compounded elastomer; low oil swell  
 Cover: Black, SBR/Nitrile blend compound for oil and ozone resistance. Convoluted.  
 Reinforcement: High tensile tire cord plies with helix wire  
 Working Pressure: 150 PSI  
 Safety Factor: 4:1  
 Temperature: -20°F to 190°F  
 Ends: Soft cuffs on standard lengths  
 Marking: PREMIUM FRAC TANK HOSE 150PSI WP NOT FOR REFINED FUELS  
 Vacuum Rating: 25 in/HG

<b>Petroleum Hose Group</b>				
<b>Frac Tank Hose</b>				
<b>Part Number</b>	<b>ID Size</b>	<b>OD Size</b>	<b>Bend Radius</b>	<b>Weight lbs per foot</b>
H-P-FRAC-128-X	8"	9"	18"	8.17
H-P-FRAC-128-39	8"	9"	18"	8.17

**For cut lengths add +15% to pricing**

For the "X" value in the part number: use "C" to specify full coil  
 use "F" to specify length in feet