

**Petroleum Hose Group**

**Fuel Transfer Hose - 200PSI**



Multi-use hose for transporting leaded, unleaded, lead substitute fuels, low pressure brake fluid or diesel fuel.

Farm and barrel pump applications, as well as construction and industrial service where UL approval is not required.

200 PSI Working Pressure.

Available in 200 foot coils.

May be available in cut lengths – please inquire.

**Tech Data:**

Tube: Black, NBR (ARPM Class A); high oil resistance  
 Cover: Black, SBR/Nitrile blend compound for oil and ozone resistance  
 Reinforcement: Spiral polyester cords  
 Working Pressure: 200 PSI  
 Safety Factor: 3:1  
 Temperature: -40°F to 190°F  
 Non-conductive: 1,800 megaOhm @ 1000 volts  
 Grounding: Embedded copper wire  
 Marking: FUEL TRANSFER HOSE (ID) 200PSI WP (white lettering)

<b>Petroleum Hose Group</b>			
<b>Fuel Transfer Hose</b>			
<b>Part Number</b>	<b>ID Size</b>	<b>OD Size</b>	<b>Weight lbs/ft</b>
H-P-FUEL-12-X	3/4"	1.06"	0.38
H-P-FUEL-16-X	1"	1.41"	0.52

For the "X" value in the part number: use "C" to specify full coil  
 use "F" to specify length in feet