

Petroleum Hose Group

Oil Discharge Hose - 200PSI



Soft wall discharge hose designed for use on trucks, docks and barges.

Standard lengths of 100 foot coils.

Also available By-the-foot and By-the-yard.

Tech Data:

Tube: Black, Nitrile, 55% aromatics (ORS)
 Cover: Black, Neoprene
 Reinforcement: 4 high tensile tire cord plies
 Working Pressure: 200 PSI
 Safety Factor: 4:1
 Temperature: -40°F to 190°F
 Static Grounding: Braided copper wire runs length of hose
 Marking: PETROLEUM TRANSFER/DISCHARGE - 200PSI WP

Petroleum Hose Group				
Oil Discharge Hose - 200 PIS				
Part Number	ID Size	OD Size	Weight lbs per foot	Price per foot
H-P-ODIS200-24-X	1 1/2"	2.00"	0.96	\$ 12.45
H-P-ODIS200-32-X	2"	2.50"	1.12	\$ 16.53
H-P-ODIS200-48-X	3"	3.50"	1.89	\$ 24.84
H-P-ODIS200-64-X	4"	4.53"	2.68	\$ 35.19
H-P-ODIS200-96-X	6"	6.84"	5.89	\$ 81.57
H-P-ODIS200-128-X	8"	9.13"	7.86	\$ 124.80

For cut lengths add +15% to pricing

**For the "X" value in the part number: use "C" to specify full coil
 use "F" to specify length in feet**