

Petroleum Hose Group

High Flexibility Oilfield Suction Hose - 150 PSI



Rugged hose for oilfield service where full suction and working pressures are required.

Convoluted cover for improved flexibility.

Not recommended for refined petroleum products.

Standard 100 foot coils. Also available By-the-foot or By-the-yard.

Tech Data:

Tube: Black, custom compounded elastomer; low oil swell
 Cover: Black, SBR/Nitrile blend compound for oil and ozone resistance. Convoluted.
 Reinforcement: High tensile tire cord plies with helix wire
 Working Pressure: 150 PSI
 Safety Factor: 4:1
 Temperature: -20°F to 180°F
 Ends: Soft cuffs on standard lengths
 Marking: OILFIELD SUCTION HOSE NOT FOR REFINED FUELS 150PSI WP
 Vacuum Rating: 30 in/HG

Petroleum Hose Group				
High Flexibility Oilfield Suction Hose				
Part Number	ID Size	OD Size	Bend Radius	Weight lbs per foot
H-P-OSU-HF-32-X	2"	2.47"	2"	1.05
H-P-OSU-HF-48-X	3"	3.50"	3"	1.64
H-P-OSU-HF-64-X	4"	4.56"	4"	2.58
H-P-OSU-HF-96-X	6"	6.80"	8"	4.75

For cut lengths add +15% to pricing

For the "X" value in the part number: use "C" to specify full coil
 use "F" to specify length in feet