

Ceramic Fiber Round Braid Rope: Premium Grade 2300°F / 1260°C: CerMax™ Extreme High Temperature, Heat & Flame Resistant



- A replacement and an alternative to asbestos. Highly flexible and minimal shrinkage.
- Melts above 3000°F / 1648°C.
- Produced from an extremely pure base fiber and can be used at 2300°F / 1260°C continuously with excursions to 3000°F / 1650°C.

CerMax™ Extreme High Temperature +Plus, Heat & Flame Resistant Ceramic Fiber Round Braided Rope: Premium Grade				
Part Number	Size		Spool length	
	inch	mm	feet	metres
R-C-B-0.250-M006-Y	.250	6	700	213
R-C-B-0.375-M010-Y	.375	10	370	112
R-C-B-0.500-M013-Y	.500	13	525	160
R-C-B-0.625-M016-Y	.625	16	350	106
R-C-B-0.750-M019-Y	.750	19	250	76
R-C-B-0.875-M022-Y	.875	22	180	54
R-C-B-1.000-M025-Y	1.000	25	125	38
R-C-B-1.250-M029-Y	1.250	32	100	30
R-C-B-1.500-M032-Y	1.500	38	75	22
R-C-B-2.000M051-Y	2.000	51	48	14

For the “Y” value in the part number: use “SP” to specify full spool
use “FT” to specify By-The-Foot

Minimum Order for this product is \$75.00 for By-The-Foot Lengths

Ceramic Twisted Fiber Rope: Premium Grade 2300°F / 1260°C: CerMax™ Extreme High Temperature, Heat & Flame Resistant



- A replacement and an alternative to asbestos. Highly flexible and minimal shrinkage.
- Melts above 3000°F / 1648°C.
- Produced from an extremely pure base fiber and can be used at 2300°F / 1260°C continuously with excursions to 3000°F / 1650°C.

CerMax™ Extreme High Temperature +Plus, Heat & Flame Resistant Ceramic Fiber Twisted Rope: Premium Grade				
Part Number	Size		Spool length	
	inch	mm	feet	metres
R-C-T-0.250-M006-Y	.250	6	900	274
R-C-T-0.375-M010-Y	.375	10	510	155
R-C-T-0.500-M013-Y	.500	13	750	228
R-C-T-0.625-M016-Y	.625	16	500	152
R-C-T-0.750-M019-Y	.750	19	375	114
R-C-T-0.875-M022-Y	.875	22	275	83
R-C-T-1.000-M025-Y	1.000	25	225	68
R-C-T-1.250-M029-Y	1.250	32	155	47
R-C-T-1.500-M032-Y	1.500	38	110	33
R-C-T-2.000-M051-Y	2.000	51	55	16

For the “Y” value in the part number: use “SP” to specify full spool
use “FT” to specify By-The-Foot

Minimum Order for this product is \$75.00 for By-The-Foot Lengths

Ceramic Fiber Square Braided Rope - Dry Packing
Premium Grade – with and without Inconel wire insert
2300°F / 1260°C: CerMax™ Extreme High Temperature, Heat & Flame Resistant



- A replacement and an alternative to asbestos. Highly flexible and minimal shrinkage.
- Melts above 3000°F / 1648°C.
- Produced from an extremely pure base fiber and can be used at 2300°F / 1260°C continuously with excursions to 3000°F / 1650°C.
- A rope with inconel wire insert is also available.

CerMax™ Extreme High Temperature, Heat & Flame Resistant Ceramic Fiber Square Braided Rope: Premium Grade				
Part Number	Size inch / mm		Spool length feet / metres	
R-C-SQ-0.250-M006-Y	.250	6	450	137
R-C-SQ-0.375-M010-X-Y	.375	10	240	73
R-C-SQ-0.500-M013-X-Y	.500	13	350	106
R-C-SQ-0.625-M016-X-Y	.625	16	250	76
R-C-SQ-0.750-M019-X-Y	.750	19	165	50
R-C-SQ-0.875-M022-X-Y	.875	22	125	38
R-C-SQ-1.000-M025-X-Y	1.000	25	100	30
R-C-SQ-1.250-M029-X-Y	1.250	32	70	21
R-C-SQ-1.500-M032-X-Y	1.500	38	50	15
R-C-SQ-2.000-M051-X-Y	2.000	51	33	10
R-C-SQ-3.000-M076-Y	3.000	76	50	15

For the “X” value in the part number: use “NW” for no wire insert; use “WW” to specify with wire insert

For the “Y” value in the part number: use “SP” for full spool; use “FT” to specify By-The-Foot

Minimum Order for this product is \$75.00 for By-The-Foot Lengths