

## Round Twisted Fiberglass Rope with PTFE Coating 550°F / 287°C: High Temperature Heat & Chemical Resistance



- PTFE Impregnation

This rope offers the advantage of a non-asbestos material with higher temperature range and with excellent resistance to almost all solvents, caustics and acids.

The base yarn is rated to 1200°F / 648°C.

PTFE melting point is 620°F / 327°C.

Used as a pump packing and stuffing box packing.

### High Temperature Heat & Chemical Resistance Fiberglass Round Twisted Rope with PTFE Coating

Part Number	OD Size inch / mm	Nominal Feet per Spool
R-FG-PT-T-M003-02	0.125 / 3	2,525
R-FG-PT-T-M006-04	0.250 / 6	1,275
R-FG-PT-T-M010-06	0.375 / 10	969
R-FG-PT-T-M013-08	0.500 / 13	523
R-FG-PT-T-M016-10	0.625 / 16	305
R-FG-PT-T-M019-12	0.750 / 19	168
R-FG-PT-T-M022-14	0.875 / 22	144
R-FG-PT-T-M025-16	1.000 / 25	114
<i>R-FG-PT-T-M032-20*</i>	1.250 / 32	77
<i>R-FG-PT-T-M038-24*</i>	1.500 / 38	50
<i>R-FG-PT-T-M051-28*</i>	2.000 / 51	27

**This Product is Available By-The-Foot Except Where Indicated**

\*These items are sold in full length spools only.

The PTFE is applied to the rope by a proprietary sinterization process. The rope is soaked repeatedly in a PTFE dispersion, dried, and then baked. The result is a PTFE coating on the rope which is soft, robust and flexible; however, it can be abrasively removed from the rope with aggressive fingernail scraping, resulting in a thinner and thinner layer of PTFE remaining with each pass. The PTFE also causes the yarns to be sealed and the small gaps between the yarns filled, resulting in an almost air-tight / liquid-tight rope.