

Square Braided PTFE Rope / Compression Packing with Graphite Impregnation

550°F / 287°C: PT-Graf™ High Temperature & Chemical Resistant



- Graphite Impregnated PTFE yarn
- Heat Resistant / Chemical Resistant
- Conformable and Resilient
- Thermally Conductive
- Self Lubricating
- pH range: 0 to 14
- Rotary pump up to 450 psi, Recip pump up to 2000 psi Valve up to 3500 psi.
- Up to 4500 FPM shaft speed
- Unique packing rope with best of both world's sealing performance where moderate temperature resistance is needed.

Used as a compression packing for pump and valve shafts and as a stuffing box packing.

High Temperature Square Braided PT-Graf™ Graphite Coated PTFE Rope			
Part Number	OD Size inch / mm	Nominal Feet per Spool	Nominal Feet per Pound
R-PTFE-GR-SQ-M003-02	0.125 / 3	520	104
R-PTFE-GR-SQ-M005-03	0.187 / 5	230	46
R-PTFE-GR-SQ-M006-04	0.250 / 6	135	27
R-PTFE-GR-SQ-M008-05	0.312 / 8	85	17
R-PTFE-GR-SQ-M010-06	0.375 / 10	60	12
R-PTFE-GR-SQ-M011-07	0.437 / 11	45	9
R-PTFE-GR-SQ-M013-08	0.500 / 13	34	6.8
R-PTFE-GR-SQ-M014-09	0.562 / 14	54	5.4
R-PTFE-GR-SQ-M016-10	0.625 / 16	44	4.4
R-PTFE-GR-SQ-M019-12	0.750 / 19	32	3.2
R-PTFE-GR-SQ-M022-14	0.875 / 22	23	2.3

This Product is Available By-The-Foot

THIS PRODUCT IS SOLD IN ONE POUND INCREMENTS