

Pure PTFE Square Braided Gasket & Compression Packing Seal Rope 550°F / 287°C: High Temperature Heat & Chemical Resistance



- Pure PTFE
- pH: 0 to 14
- Up to 2500 psi
- Shaft speed up to 1600 feet per minute
- Use in corrosive and “clean” applications

This pure PTFE square rope offers the advantage of a non-asbestos material with high temperature range and with excellent resistance to almost all solvents, caustics and acids.

PTFE melting point is 620°F / 327°C.
 Used as a pump packing and stuffing box packing

Pure PTFE Square Braid Rope / Packing High Temperature & Chemical Resistance			
Part Number	OD Size inch / mm	Nominal Feet per Spool	Nominal Feet per Pound
R-PTFE-SQ-0.125-M003-X	0.125 / 3	415	83
R-PTFE-SQ-0.187-M005-X	0.187 / 5	180	36
R-PTFE-SQ-0.250-M006-X	0.250 / 6	102	20.4
R-PTFE-SQ-0.312-M008-X	0.312 / 8	68	13.6
R-PTFE-SQ-0.375-M010-X	0.375 / 10	46	9.3
R-PTFE-SQ-0.437-M011-X	0.437 / 11	34	6.9
R-PTFE-SQ-0.500-M013-X	0.500 / 13	26	5.3
R-PTFE-SQ-0.562-M014-X	0.562 / 14	42	4.2
R-PTFE-SQ-0.625-M016-X	0.625 / 16	35	3.5
R-PTFE-SQ-0.750-M019-X	0.750 / 19	23	2.36
R-PTFE-SQ-0.875-M022-X	0.875 / 22	17	1.76

THIS PRODUCT IS SOLD IN ONE POUND INCREMENTS