

Silicone Sponge Cord - High Temperature & Heat Resistant 392°F / 200°C



- Suitable for continuous operation from -80°F (-62°C) to 392°F (200°C).
- Depending on media and application useful life at temperatures up to 425°F (218°C) may be obtained.
- Density 16lb per cubic foot
- Compression recovery; 25% deflection: 100% at room temperature. Slightly reduced at elevated temperatures
- Thermal value: 0.0695 W(M.K)
- Tensile strength 65 Newtons

FlameShield™ High Temperature, Heat & Flame Resistant Silicone Sponge Cord			
Size: .062" to 1.000" (1.8mm to 14.3mm)			
Part Number	Diameter in / mm	Spool Length ft / m	Color
R-SSC-0.062-M0016	.062 / 1.57	50 / 15.24	Blue
R-SSC-0.125-M0031	.125 / 3.17	50 / 15.24	Black
R-SSC-0.187-M0047	.187 / 4.74	50 / 15.24	Red
R-SSC-0.218-M0055	.218 / 5.53	50 / 15.24	Red
R-SSC-0.250-M0063	.250 / 6.35	50 / 15.24	Grey
R-SSC-0.312-M0079	.312 / 7.92	50 / 15.24	Blue
R-SSC-0.375-M0095	.375 / 9.52	50 / 15.24	Red
R-SSC-0.437-M0110	.437 / 11.09	50 / 15.24	Grey
R-SSC-0.500-M0127	.500 / 12.70	25 / 7.62	Orange
R-SSC-0.625-M0158	.625 / 15.87	25 / 7.62	Grey
R-SSC-0.750-M0190	.750 / 19.05	25 / 7.62	Red
R-SSC-0.875-M0222	.875 / 22.22	25 / 7.62	Grey
R-SSC-1.000-M0254	1.000 / 25.40	25 / 7.62	Blue