

## High Alumina Content Braided Ceramic Sleeve 2190°F / 1199°C: AluMax™ High Temperature & Heat Resistant Sleeve



- Soft and pliable. Asbestos free.
- Cuts easily to length with scissors.
- This is a braided sleeve and has a small amount of expandibility.
- Highest temperature rated sleeve available.
- Fabricated from continuous filament fibers.
- Boron free.
- Wall Thickness: 1/64" sleeve: 0.008"; 1/32" sleeve: 0.010"; 1/16" sleeve: 0.028"; 1/8" through 3" ID: 0.035"
- May contain 2 lengths per spool. Add 15% for continuous length.
- Heat Cleaned / Heat Treated version available – add 15%.
- Other spool lengths available – please enquire.
- Dimension is nominal – may vary +/-5%.

2190°F / 1199°C continuous rating, high insulation value

AluMax™ High Temperature & Heat Resistant Braided Alumina Sleeve - Premium		
Part Number	Nominal ID inch / mm	Spool Length Ft / m
S-ALUMINA-0.015-M00039	1/64 / 0.39	100 / 30
S-ALUMINA-0.031-M00079	1/32" / 0.79	100 / 30
S-ALUMINA-0.062-M00158	1/16 / 1.58	100 / 30
S-ALUMINA-0.125-M00317	1/8" / 3.17	100 / 30
S-ALUMINA-0.187-M00476	3/16" / 4.76	100 / 30
S-ALUMINA-0.250-M00635	1/4" / 6.35	50 / 15
S-ALUMINA-0.312-M00793	5/16" / 7.93	50 / 15
S-ALUMINA-0.375-M00952	3/8" / 9.52	50 / 15
S-ALUMINA-0.500-M0127	1/2" / 12.7	50 / 15
S-ALUMINA-0.625-M0158	5/8" / 15.8	50 / 15
S-ALUMINA-0.750-M0190	3/4" / 19.0	50 / 15
S-ALUMINA-1.000-M0254	1" / 25.4	25 / 7.5
S-ALUMINA-1.500-M0381	1 1/2" / 38.1	25 / 7.5
S-ALUMINA-2.000-M051	2" / 51	25 / 7.5
S-ALUMINA-2.500-M064	2 1/2" / 64	25 / 7.5
S-ALUMINA-3.000-M076	3" / 76	25 / 7.5

This product is made to order - please allow 4 to 6 business days for production

## High Alumina Content Braided Ceramic Sleeve – Thick Wall

### 2190°F / 1199°C: AluMax™ High Temperature & Heat Resistant Sleeve



- Soft and pliable. Asbestos free.
- Cuts easily to length with scissors.
- This is a braided sleeve and has a small amount of expandibility.
- Highest temperature rated sleeve available.
- Fabricated from continuous filament fibers.
- Boron free.
- Wall Thickness of 0.125":
- Heat Cleaned / Heat Treated version available – add 15%.
- Other spool lengths available – please enquire.
- Dimension is nominal – may vary +/-5%.

2190°F / 1199°C continuous rating, high insulation value

AluMax™ High Temperature & Heat Resistant Braided Alumina Sleeve - Premium		
Part Number	Nominal ID inch / mm	Spool Length Ft / m
S-ALUMINA-HDW-0.500-M0127	1/2" / 12.7	50 / 15
S-ALUMINA-HDW-0.750-M0190	3/4" / 19.0	50 / 15
S-ALUMINA-HDW-1.000-M0254	1" / 25.4	25 / 7.5
S-ALUMINA-HDW-1.500-M0381	1 1/2" / 38.1	25 / 7.5

This product is made to order - please allow 4 to 6 business days for production

## High Alumina Content Braided Ceramic Sleeve – XT (extended temperature) 2370°F / 1298°C: AluMax™ High Temperature & Heat Resistant Sleeve



- Soft and pliable. Asbestos free.
- Cuts easily to length with scissors.
- This is a braided sleeve and has a small amount of expandibility.
- Highest temperature rated sleeve available.
- Fabricated from continuous filament fibers.
- Boron free.
- Wall Thickness: 1/64" sleeve: 0.008"; 1/32" sleeve: 0.010"; 1/16" sleeve: 0.028"; 1/8" through 3" ID: 0.035"
- May contain 2 lengths per spool. Add 15% for continuous length.
- Heat Cleaned / Heat Treated version available – add 15%.
- Other spool lengths available – please enquire.
- Dimension is nominal – may vary +/-5%.

2370°F / 1298°C continuous rating, high insulation value

AluMax™ Extended High Temperature & Heat Resistant Braided Alumina Sleeve - Premium		
Part Number	Nominal ID inch / mm	Spool Length Ft / m
S-ALUMINA-XT-0.015-M00039	1/64 / 0.39	100 / 30
S-ALUMINA-XT-0.031-M00079	1/32" / 0.79	100 / 30
S-ALUMINA-XT-0.062-M00158	1/16 / 1.58	100 / 30
S-ALUMINA-XT-0.125-M00317	1/8" / 3.17	100 / 30
S-ALUMINA-XT-0.187-M00476	3/16" / 4.76	100 / 30
S-ALUMINA-XT-0.250-M00635	1/4" / 6.35	50 / 15
S-ALUMINA-XT-0.312-M00793	5/16" / 7.93	50 / 15
S-ALUMINA-XT-0.375-M00952	3/8" / 9.52	50 / 15
S-ALUMINA-XT-0.500-M0127	1/2" / 12.7	50 / 15
S-ALUMINA-XT-0.625-M0158	5/8" / 15.8	50 / 15
S-ALUMINA-XT-0.750-M0190	3/4" / 19.0	50 / 15
S-ALUMINA-XT-1.000-M0254	1" / 25.4	25 / 7.5
S-ALUMINA-XT-1.500-M0381	1 1/2" / 38.1	25 / 7.5
S-ALUMINA-XT-2.000-M051	2" / 51	25 / 7.5
S-ALUMINA-XT-2.500-M064	2 1/2" / 64	25 / 7.5
S-ALUMINA-XT-3.000-M076	3" / 76	25 / 7.5

This product is made to order - please allow 4 to 6 business days for production

## High Alumina Content Braided Ceramic Sleeve – Thick Wall – XT (extended temperature) 2370°F / 1298°C: AluMax™ High Temperature & Heat Resistant Sleeve



- Soft and pliable. Asbestos free.
- Cuts easily to length with scissors.
- This is a braided sleeve and has a small amount of expandibility.
- Highest temperature rated sleeve available.
- Fabricated from continuous filament fibers.
- Boron free.
- Wall Thickness of 0.125":
- Heat Cleaned / Heat Treated version available – add 15%.
- Other spool lengths available – please enquire.
- Dimension is nominal – may vary +/-5%.

2370°F / 1298°C continuous rating, high insulation value

AluMax™ Extended High Temperature & Heat Resistant Braided Alumina Sleeve - Premium		
Part Number	Nominal ID inch / mm	Spool Length Ft / m
S-ALUMINA-XT-HDW-0.500-M0127	1/2" / 12.7	50 / 15
S-ALUMINA-XT-HDW-0.750-M0190	3/4" / 19.0	50 / 15
S-ALUMINA-XT-HDW-1.000-M0254	1" / 25.4	25 / 7.5
S-ALUMINA-XT-HDW-1.500-M0381	1 1/2" / 38.1	25 / 7.5

This product is made to order - please allow 4 to 6 business days for production