

## Braided Carbon Fiber Sleeve

1000°F / 537°C: Continuous Rating – Higher Temperature for Shorter Periods  
High Temperature & Heat Resistant



Available in 0.013", 0.020" and 0.030" wall thickness.

Used to fabricate tubular structures that are lightweight and strong.

The cut ends will fray – standard anti-fray techniques can be used such as metal wire or clamps.

## Braided Carbon Fiber Sleeve (Continued)

1000°F / 537°C: Continuous Rating – Higher Temperature for Shorter Periods

High Temperature & Heat Resistant

FlameShield™ High Temperature & Heat Resistant Carbon Fiber Sleeve			
Part Number	Nominal ID	Size Range	Spool Length in feet Bulk / Small
<b>Light Wall 0.013" replace "X" in part number with "LW"</b>			
S-CF-M006-04-X	1/4" / 6 mm	1/8" to 5/16"	500 / 100
S-CF-M013-08-X	1/2" / 13 mm	1/4" to 5/8"	250 / 50
S-CF-M019-12-X	3/4" / 19 mm	5/16" to 7/8"	250 / 50
S-CF-M025-16-X	1" / 25 mm	3/8" to 1 1/16"	200 / 50
S-CF-M032-20-X	1 1/4" / 32 mm	1/2" to 1 1/2"	125 / 25
S-CF-M038-24-X	1 1/2" / 38 mm	5/8" to 1 3/4"	100 / 25
S-CF-M051-32-X	2" / 51 mm	3/4" to 2 3/16"	100 / 25
<b>Medium Wall 0.020" replace "X" in part number with "MW"</b>			
S-CF-M013-08-X	1/2" / 13 mm	1/4" to 5/8"	250 / 50
S-CF-M019-12-X	3/4" / 19 mm	5/16" to 7/8"	250 / 50
S-CF-M025-16-X	1" / 25 mm	7/16" to 1 1/16"	200 / 50
S-CF-M032-20-X	1 1/4" / 32 mm	9/16" to 1 1/2"	125 / 25
S-CF-M038-24-X	1 1/2" / 38 mm	3/4" to 1 3/4"	100 / 25
S-CF-M051-32-X	2" / 51 mm	7/8" to 2 3/16"	100 / 25
S-CF-M064-40-X	2 1/2" / 64 mm	1 1/16" to 3"	100 / 25
<b>Heavy Wall 0.030" replace "X" in part number with "HW"</b>			
S-CF-M019-12-X	3/4" / 19 mm	3/8" to 7/8"	250 / 50
S-CF-M025-16-X	1" / 25 mm	1/2" to 1 1/16"	200 / 50
S-CF-M032-20-X	1 1/4" / 32 mm	11/16" to 1 1/2"	125 / 25
S-CF-M038-24-X	1 1/2" / 38 mm	13/16" to 1 3/4"	100 / 25
S-CF-M051-32-X	2" / 51 mm	1" to 2 3/16"	100 / 25
S-CF-M064-40-X	2 1/2" / 64 mm	1 1/4" to 3"	100 / 25
S-CF-M076-48-X	3" / 76 mm	1 1/2" to 3 1/2"	50 / 25

**For the "X" value:  
use "B" for Bulk Spool size, use "S" for Small Spool size**