



**EMI / RFI Shielding Sleeve with Snap Closure**  
**302°F / 150°C Maximum Continuous Exposure**



- Easy to install PVC sleeve with snap closure.
- Aluminized internal layer is connected to an earthing drain 15 AWG tinned copper braid for connection to ground at one end of the sleeve or both.
- Available as a 50 or 164 foot roll length.
- Sleeve may be easily cut to length and be installed/removed without disconnection of wiring or cables.
- Flexible to -70°F / -57°C.

PVC with Aluminized Side and Earthing Drain Wire for EMI/RFI Protection - Plastic Snap Closure		
Part Number	Inside Diameter inch / mm / dash#	Price / Foot
S-EMIRFI-PVC-SNAP-M010-06-X	0.375 / 10 / -06	\$ call
S-EMIRFI-PVC-SNAP-M013-08-X	0.50 / 13 / -08	\$ call
S-EMIRFI-PVC-SNAP-M019-12-X	0.75 / 19 / -12	\$ call
S-EMIRFI-PVC-SNAP-M025-16-X	1.00 / 25 / -16	\$ call
S-EMIRFI-PVC-SNAP-M028-18-X	1.125 / 28 / -18	\$ call
S-EMIRFI-PVC-SNAP-M038-24-X	1.50 / 38 / -24	\$ call
S-EMIRFI-PVC-SNAP-M051-32-X	2.00 / 51 / -32	\$ call
S-EMIRFI-PVC-SNAP-M070-44-X	2.75 / 70 / -44	\$ call
S-EMIRFI-PVC-SNAP-M101-64-X	4.00 / 101 / -64	\$ call
Other custom sizes available – please enquire		

For the “X” value: use “B” for 164 foot spool size, use “S” for 50 foot spool size