

Braided Fiberglass Sleeve with Graphite Impregnation
1200°F / 648°C: Continuous Rating – Higher Temperature for Shorter Periods
DeltaGlass™: High Temperature & Heat Resistant



- 1/16" and 1/8" wall thickness
- Graphite Impregnation

Graphite adds lubrication to result in a very slippery sleeve but does not add electrical conductivity.

Resists molten splash and weld splatter as it cannot stick to the graphite.

1200°F / 648°C continuous rating, high insulation value & excellent personnel protection

Very High-Temperature Braided Sleeve with Graphite Coating				
Part Number	Size			Feet per Spool Thin wall / Thick wall
	in	mm	-dash	
S-FG-GC-M006-04-X	.250	6	-04	1400 / 700
S-FG-GC-M010-06-X	.375	10	-06	1400 / 600
S-FG-GC-M013-08-X	.500	13	-08	1000 / 330
S-FG-GC-M016-10-X	.625	16	-10	900 / 315
S-FG-GC-M019-12-X	.750	19	-12	750 / 300
S-FG-GC-M022-14-X	.875	22	-14	650 / 300
S-FG-GC-M025-16-X	1.000	25	-16	500 / 290
S-FG-GC-M032-20-X	1.250	32	-20	450 / 280
S-FG-GC-M038-24-X	1.500	38	-24	350 / 225
S-FG-GC-M041-26-X	1.625	41	-26	300 / 208
S-FG-GC-M044-28-X	1.750	44	-28	300 / 208
S-FG-GC-M051-32-X	2.000	51	-32	250 / 190
S-FG-GC-M057-36-X	2.250	57	-36	250 / 190
S-FG-GC-M064-40-X	2.500	64	-40	225 / 180
S-FG-GC-M070-44-X	2.750	70	-44	225 / 180
S-FG-GC-M076-48-X	3.000	76	-48	200 / 175
S-FG-GC-M083-52-X	3.250	83	-52	200 / 175
S-FG-GC-M089-56-X	3.500	89	-56	190 / 170
S-FG-GC-M095-60-X	3.750	95	-60	190 / 170
S-FG-GC-M102-64-X	4.000	102	-64	175 / 140
S-FG-GC-M114-72-X	4.500	114	-72	175 / 140
S-FG-GC-M127-80-X	5.000	127	-80	120 / 100

For the "X" value, use "A" to specify Thin Wall; use "B" to specify Thick Wall

Thin Wall = 1/16" / 1.59mm • Thick Wall = 1/8" / 3.18mm

This Product is Available By The Foot