

Fiberglass Fabric with PTFE Resin Coating Sleeve with VELCRO® Brand Hook & Loop Closure

550°F / 287°C: Continuous Rating – Higher Temperature for Shorter Periods
Scuff-Sleeve™ VC



- Specialty protection for hoses, wire and cables.
- Sleeve with Velcro for easy retrofit.
- Sleeve is made from fiberglass base fabric impregnated with a PTFE resin coating. Excellent chemical resistance. Temperature range - 60°F to +550°F. Excellent UV protection. Not for use near open flame or welding.
- Used for food processing robot cables, lines and hoses.
- Washdown resistant
- Removeable for machine cleaning

Fiberglass Fabric with PTFE Resin Coating Sleeve with VELCRO® Brand Closure (Continued)
550°F / 287°C: Continuous Rating – Higher Temperature for Shorter Periods
Scuff-Sleeve™ VC



Sold in 50 foot increments up to 150 feet continuous rolls. Available in standard sizes; larger or custom sizes can be easily fabricated if required. Helps to organize and bundle hoses and cables.

Scuff-Sleeve™ VC: PTFE Impregnated Fiberglass Fabric Specialty Protection Sleeve with VELCRO® Brand Hook & Loop Closure			
Part Number	Size inch / mm / -dash		
S-FG-PTFE-VCL-M025-16 *	1.00	25	-16
S-FG-PTFE-VCL-M051-32	2.00	51	-32
S-FG-PTFE-VCL-M064-40	2.50	64	-40
S-FG-PTFE-VCL-M070-44	2.75	70	-44
S-FG-PTFE-VCL-M076-48	3.00	76	-48
S-FG-PTFE-VCL-M083-52	3.25	83	-52
S-FG-PTFE-VCL-M089-56	3.50	89	-56
S-FG-PTFE-VCL-M102-64	4.00	102	-64
S-FG-PTFE-VCL-M127-80	5.00	127	-80
S-FG-PTFE-VCL-M152-96	6.00	152	-96
S-FG-PTFE-VCL-M178-112	7.00	165	-104
S-FG-PTFE-VCL-M203-128	8.00	203	-128

Custom sizes available

Width of the Velcro is 1.5" except part numbers indicated with (*) which is .75".