

## Solid Wall Stainless Steel Flexible Sleeve 304 / 321

1200°F / 648°C:



- Annular corrugated construction provides ability to easily flex and bend, compress and expand.
- Excellent abrasion and splash Protection.
- EMI / RFI Shield.
- Provides Blow-out protection for hydraulic hoses.
- Provides rodent protection for burial cables and hoses.
- Wires cables and hoses can be spiral wrapped with tapes prior to insertion for insulation spacing to the sidewall.
- Range of fittings and connection flanges available to terminate sleeve onto metalwork, bulkheads, etc.
- Available in Bronze, Monel, Inconel & Hastelloy.

Solid Wall Stainless Steel Flexible Sleeve – 304 / 321						
Part Number	Nominal ID inch / mm		Min Bend Radius inch		Weight per foot	Mill Lengths feet
			Static	Dynamic		
S-M-SS321-SW-0.32-M008	.32	8	4	6	0.09	30-100
S-M-SS304-SW-0.42-M011	.42	11	2	4	0.12	30-100
S-M-SS304-SW-0.52-M013	.52	13	3	5	0.16	30-100
S-M-SS304-SW-0.81-M020	.81	20	4	6	0.26	30-100
S-M-SS304-SW-1.03-M026	1.03	26	4.5	7	0.36	30-100
S-M-SS304-SW-1.30-M033	1.30	33	4	11	0.45	30-60
S-M-SS304-SW-1.53-M039	1.53	39	4.5	12	0.48	30-60
S-M-SS304-SW-2.05-M052	2.05	52	5	13	0.70	30-60
S-M-SS304-SW-2.61-M066	2.61	66	5	13	1.28	7-20
S-M-SS304-SW-3.10-M079	3.10	79	7.5	16	1.53	7-20
S-M-SS321-SW-3.50-M089	3.50	89	8	17	1.65	7-20
S-M-SS304-SW-3.98-M101	3.98	101	10	20	1.95	7-20
S-M-SS304-SW-5.03-M128	5.03	128	12	24	2.76	7-20
S-M-SS304-SW-5.98-M152	5.98	152	15	30	3.34	7-20
S-M-SS304-SW-7.96-M202	7.96	202	20	40	5.32	5-12
S-M-SS304-SW-9.78-M248	9.78	248	25	50	8.71	5-12
S-M-SS304-SW-11.76-M299	11.76	299	30	60	11.58	5-12
S-M-SS304-SW-13.62-M346	13.62	346	35	70	14.57	5-12

This Product is Available By-The-Foot

Supplied in 304SS as standard. Except (\*) supplied in 321SS

Also Available in 321 & 316 Stainless, Bronze, Monel, Inconel and Hastelloy, please call for pricing