

Nomex® Braided Sleeve

450°F / 232°C: Continuous Rating – Higher Temperature for Shorter Periods
FlameShield™ High Temperature, Heat & Flame Resistant Expandable Sleeve – Premium Grade



- Genuine Dupont Nomex®
- Soft and pliable.
- Halogen & asbestos free.
- 90,000 psi tensile strength.
- Cuts easily to length with scissors. Braid angle allows this sleeve to expand slightly to accommodate irregular surfaces and turns, splices and in-line connectors.
- Available in natural and green color.
- .016" wall thickness.
- 662°F / 350°C melting/deterioration temperature.

450°F / 232°C continuous rating, high insulation value & excellent personnel protection

FlameShield™ Braided Nomex® Sleeve High Temperature & Heat Resistant – Premium Grade		
Part Number	Nominal ID	Size Range
S-NMX-0.125-M003-02-X-Y	1/8"	1/16" to 1/4"
S-NMX-0.250-M006-04-X-Y	1/4"	1/8" to 5/16"
S-NMX-0.312-M008-05-X-Y	5/16"	7/32" to 7/16"
S-NMX-0.375-M010-06-X-Y	3/8"	1/4" to 1/2"
S-NMX-0.500-M013-08-X-Y	1/2"	5/16" to 5/8"
S-NMX-0.625-M016-10-X-Y	5/8"	7/16" to 7/8"
S-NMX-0.750-M019-12-X-Y	3/4"	9/16" to 1"
S-NMX-1.000-M025-16-X-Y	1"	3/4" to 1 1/8"
S-NMX-1.250-M032-20-X-Y	1 1/4"	1" to 1 1/2"
S-NMX-1.500-M038-24-X-Y	1 1/2"	1 1/4" to 1 3/4"
S-NMX-1.750-M044-28-X-Y	1 3/4"	1 1/2" to 2"

For the "X" value, use "100" for 100 foot spool, use "25" for 25 foot spool

For the "Y" value, use "NT" natural color, use "GN" for green color

Please call for additional discount pricing when ordering multiple spools.

This Product is NOT Available By-The-Foot – Spools Only