

Abrasion & Wear Resistant Nylon 6-6 Braided Sleeve
.050 Flattened Monofilament Construction
Extremely high abrasion resistance for Hose, Wire and Cable Protection



- Abrasion and wear resistant protection sleeve for hoses, wires and cables.
- Made from flattened 50 mil (.050") monofilament nylon 6-6 – provides a tight weave and smooth surface resists abrasive wear.
- Expandable.
- Nylon 6 provides excellent UV protection.
- Easily cut to length with heat knife.
- Minimum temperature: -76°F / -60°C. Maximum continuous 302°F / 150°C (MIL-I-23053). Melting temperature 509°F / 265°C.
- 4400 abrasion cycle rated



Scuff-Sleeve™ Braided Nylon Expandable Protection Sleeve Fabricated from Flattened .050 Monofilament			
Part Number	Nominal Size	Range	Spool Size Bulk / Shop Spool
S-NY-APS-ES50-0.50-M013-08-X	0.50"	0.375 – 0.625	500 ft / 100 ft
S-NY-APS-ES50-0.75-M019-12-X	0.75"	0.625 – 1.00	250 ft / 50 ft
S-NY-APS-ES50-1.00-M025-16-X	1.00"	0.975 – 1.25"	250 ft / 50 ft
S-NY-APS-ES50-1.25-M032-20-X	1.25"	1.00 – 1.50	250 ft / 50 ft
S-NY-APS-ES50-1.75-M044-28-X	1.75"	1.50 – 2.00	100 ft / 25 ft
S-NY-APS-ES50-2.00-M057-36-X	2.00"	1.75 – 2.75	100 ft / 25 ft

For the "X" value in the part number: specify "B" for Bulk Spool or "S" for Shop Spool