Nylon Abrasion & Wear Protection Braided Sleeve MIL Spec with thick wall

375°F / 190°C: Abrasion & Wear Resistant Scuff-Sleeve™: for Hose, Wire and Cable Protection Meets A-A-59301 & MIL-C-572 Specifications

- Heavy Wall version of S-NY-APS-MIL sleeve.
- Abrasion, wear, puncture and cut resistant protection sleeve for hoses, wires and cables.
- Conforms to A-A-59301 and MIL-C-572 specifications.
- Tight weave and smooth surface resists abrasive wear.
- Nylon 6 provides excellent UV protection.
- Easily cut to length or cut with heat knife.
- Useable -60°F to +375°F.
- Helps to organize and bundle hoses and cables, while proving heat resistance to a maximum of 375°F continuous duty, and provides excellent abrasion, scuff and wear resistance

Scuff-Sleeve™ Nylon Abrasion & Wear Protection Sleeve – Heavy Wall
Meets A-A-59301 and MIL-C-572 Specifications

Part Number	ID Size inch / mm / -dash			Wall Thickness	Spool Feet
S-NY-APS-MILHD-M005-03	3/16	4.76	-03	.030	500
S-NY-APS-MILHD-M006-04	1/4	6.35	-04	.030	500
S-NY-APS-MILHD-M008-05	5/16	7.93	-05	.030	500
S-NY-APS-MILHD-M010-06	3/8	9.52	-06	.030	250
S-NY-APS-MILHD-M011-07	7/16	11.12	-07	.030	250
S-NY-APS-MILHD-M013-08	1/2	12.7	-08	.030	250
S-NY-APS-MILHD-M016-10	5/8	15.87	-10	.040	150 / 250
S-NY-APS-MILHD-M019-12	3/4	19.05	-12	.040	150 / 250
S-NY-APS-MILHD-M022-14	7/8	22.22	-14	.040	100 / 250
S-NY-APS-MILHD-M025-16	1	25.4	-16	.050	100 / 250

- Other lengths may be available: please enquire.
- This sleeve is non-expandable – please measure your application carefully.