

## Multicomp PRO Series PP00 Equivalent Sleeving

High Temperature, Heat, Flame, Fire & Molten Metal Resistant  
Protection for Pipes, Hoses, Cables and Wires

500°F / 260°C Continuous Rating – Higher Temperature for Shorter Periods  
*Silicone Rubber Coated Fiberglass Sleeve for Industrial Use*



### Protection from:

- Heat
- Flame
- Fire
- Molten Metal Splash
- Welding Splatter & Sparks

**Multicomp PRO** equivalent sleeve is heat, flame and fire protection for hoses, tubing, cables and wiring in harsh industrial environments.

Utilized in most industries with hot processes, liquid metal or welding operations to protect assets and prevent failures, prolonging the life of critical hoses, wires and cables, and reduce unexpected shutdowns.

Also protects personnel from hot or cold hoses and pipes.

Can be double sleeved or undersleeved with uncoated braided or knitted sleeves for additional thermal protection.

This sleeving has some radial elasticity (approx 15%), allowing it to pass over splices and connectors.

Also used to cover water-cooled high current EAF cables and cooling water hoses at metal processing plants due to the excellent molten metal splash and slag protection.

Extremely flexible, pliable and conformable. Used for fuel, brake, oil and hydraulic line / hose protection on mobile construction equipment, mining equipment, rail cars, buses and emergency response vehicles.

An excellent cold temperature sleeve with flexibility to -76°C. Further material specifications available.

Fabricated from a E-type glass yarn that is **braided**. It then receives a thick coating of self-extinguishing silicone rubber that withstands liquid metal splash, flame, slag, sparks, and other hazards in the toughest of environments.

Standard lengths are 25, 50 & 100 feet; specific cut lengths are available.

Standard color is orange. Other colors are available subject to minimum order.

RoHS Compliant

## Multicomp PRO PP00 Series Equivalent Sleeving

500°F / 260°C continuous rating with weld splatter / molten metal splash protection.  
 2200°F / 1205°C for periods up to 15 minutes and short excursions to 3000°F / 1650°C.

<b>Multicomp PRO PP00 Series Equivalent Sleeving</b>					
Nominal ID Inches / mm / Dash #			Part Number	Price per Foot	Price per Metre
1/4	6	-04	S-PP001427-X	\$ 3.57	\$ 11.71
5/16	8	-05	S-PP001428-X	\$ 3.68	\$ 12.07
3/8	10	-06	S-PP001429-X	\$ 3.90	\$ 12.79
7/16	11	-07	S-PP00-07-X	\$ 4.16	\$ 13.64
1/2	12	-08	S-PP001430-X	\$ 4.62	\$ 15.15
9/16	15	-09	S-PP001431-X	\$ 4.80	\$ 15.74
5/8	16	-10	S-PP00-10-X	\$ 4.95	\$ 16.24
11/16	17	-11	S-PP00-11-X	\$ 5.37	\$ 17.61
3/4	19	-12	S-PP00-12-X	\$ 5.66	\$ 18.56
13/16	20	-13	S-PP001432-X	\$ 6.29	\$ 20.63
7/8	22	-14	S-PP00-14-X	\$ 6.71	\$ 22.01
1	25	-16	S-PP001433-X	\$ 7.62	\$ 24.99
1 1/8	30	-18	S-PP001434-X	\$ 8.61	\$ 28.24
1 1/4	32	-20	S-PP00-20-X	\$ 9.20	\$ 30.18
1 3/8	35	-22	S-PP001435-X	\$ 9.28	\$ 30.44
1 1/2	38	-24	S-PP00-24-X	\$ 9.55	\$ 31.32
1 5/8	40	-26	S-PP001436-X	\$ 9.69	\$ 31.78
1 3/4	45	-28	S-PP001437-X	\$ 11.26	\$ 36.93
1 7/8	48	-30	S-PP00-30-X	\$ 12.69	\$ 41.62
2	50	-32	S-PP001438-X	\$ 14.98	\$ 49.13
2 1/4	55	-36	S-PP001439-X	\$ 16.81	\$ 55.14
2 3/8	60	-38	S-PP001440-X	\$ 19.44	\$ 63.76
2 1/2	65	-40	S-PP001441-X	\$ 22.08	\$ 72.42
2 5/8	67	-42	S-PP00-42-X	\$ 24.40	\$ 80.03
2 3/4	70	-44	S-PP001442-X	\$ 26.71	\$ 87.61
2 7/8	73	-46	S-PP00-46-X	\$ 28.12	\$ 92.23
3	75	-48	S-PP001443-X	\$ 29.53	\$ 96.86
3 1/8	80	-50	S-PP001444-X	\$ 30.74	\$ 100.83
3 1/4	85	-52	S-PP001445-X	\$ 31.94	\$ 104.76
3 1/2	90	-56	S-PP001446-X	\$ 34.24	\$ 112.31
3 3/4	95	-60	S-PP00-60-X	\$ 36.25	\$ 118.90
4	100	-64	S-PP001447-X	\$ 38.58	\$ 116.70
4 1/2	114	-72	S-PP001448-X	\$ 45.30	\$ 148.58
5	127	-80	S-PP001449-X	\$ 48.76	\$ 159.93

For the "X" value – use "OR" to specify Oxide-red color or use "BK" for Black

Discounts available for 15 & 30 Metre lengths