

Silicone Rubber Tubing; High Temperature & Heat Resistant 460°F / 237°C: Premium Grade – Natural / Translucent



Variety of uses including air, gas and liquid transfer.

Can be used to mask threads and posts for powder coating painting applications.

Good elasticity to fit over pipe nipples.

Hardness: 50 +/-5, Tensile: >1000 psi,
 Elongation: >400%, Tear Strength: >100 lbs/in,
 Specific Gravity: <1.7, Electrical Resistance: 24kV/mm,
 Electrical Volume Resistivity: 1 x 10 ohm/cm

500°F / 260°C continuous rating

High Temperature, Heat & Flame Resistant Silicone Rubber Tubing Premium Natural / Clear			
Part Number	Inside Diameter in / mm	Wall Thickness in / mm	Coiled Length ft / m
SR-TUBE-NAT-ID040-W06	.040 / 1.02	.060 / 1.50	100 / 30.48
SR-TUBE-NAT-ID062-W06	.062 / 1.57	.060 / 1.50	100 / 30.48
SR-TUBE-NAT-ID080-W06	.080 / 2.03	.060 / 1.50	100 / 30.48
SR-TUBE-NAT-ID093-W06	.093 / 2.36	.060 / 1.50	100 / 30.48
SR-TUBE-NAT-ID109-W06	.109 / 2.77	.060 / 1.50	100 / 30.48
SR-TUBE-NAT-ID125-W06	.125 / 3.18	.060 / 1.50	100 / 30.48
SR-TUBE-NAT-ID140-W06	.140 / 3.56	.060 / 1.50	100 / 30.48
SR-TUBE-NAT-ID156-W06	.156 / 3.96	.060 / 1.50	100 / 30.48
SR-TUBE-NAT-ID172-W06	.172 / 4.37	.060 / 1.50	100 / 30.48
SR-TUBE-NAT-ID187-W06	.187 / 4.75	.060 / 1.50	100 / 30.48
SR-TUBE-NAT-ID203-W06	.203 / 5.16	.060 / 1.50	100 / 30.48
SR-TUBE-NAT-ID218-W06	.218 / 5.54	.060 / 1.50	100 / 30.48
SR-TUBE-NAT-ID234-W06	.234 / 5.94	.060 / 1.50	100 / 30.48
SR-TUBE-NAT-ID250-W06	.250 / 6.35	.060 / 1.50	100 / 30.48
SR-TUBE-NAT-ID281-W06	.281 / 7.14	.060 / 1.50	100 / 30.48
SR-TUBE-NAT-ID312-W06	.312 / 7.92	.060 / 1.50	100 / 30.48

This Product is NOT Available By-The-Foot – Full Coil Quantity Only

These silicone rubber products provide excellent cold temperature performance with flexibility to -76°C for refrigeration and cryogenic applications.