

InsulShrink™ Polyolefin Fuel Resistant Shrink Tubing

2:1 shrink ratio - 194°F / 90°C Shrink Temperature



- Good general chemical resistance.
- Easily cut to length.
- Excellent UV resistance
- Shrink temperature 239F

InsulShrink™ Polyolefin Fuel Resistant Heatshrink Tubing 2:1 shrink ratio			
Part Number	Shrink Range Preshrunk → Shrunk	Length, ft	
		Bulk Box / Small Box	
ST-P2-HC-0.125-BK-Y	0.125 → 0.062	500	25
ST-P2-HC-0.187-BK-Y	0.187 → 0.093	250	25
ST-P2-HC-0.250-BK-Y	0.250 → 0.125	250	25
ST-P2-HC-0.375-BK-Y	0.375 → 0.187	200	25
ST-P2-HC-0.500-BK-Y	0.500 → 0.250	100	25
ST-P2-HC-0.750-BK-Y	0.750 → 0.375	100	25
ST-P2-HC-1.000-BK-Y	1.000 → 0.500	100	25
ST-P2-HC-1.250-BK-Y	1.250 → 0.625	100	25
ST-P2-HC-1.500-BK-Y	1.500 → 0.750	100	25

Available in Black

For the “Y” value in the part number: specify “B” for Bulk Box or “S” for Small Box