

InsulShrink™ PVC Heat Shrink Tubing – Clear / Black

2:1 shrink ratio - 392°F / 200°C Maximum Operating Temperature



- Good general chemical resistance.
- Available in clear or black.
- Easily cut to length.



InsulShrink™ Clear / Black PVC Heat-Shrink Tubing - 2:1 shrink ratio			
Part Number	Shrink Range Not Shrunk → Shrunk	Spool Size	
		Bulk Spool	Shop Spool
ST-PVC2-0.062-XX-Y	1.6mm → 0.8mm	1000 ft	100 ft
ST-PVC2-0.250-XX-Y	6.4mm → 3.2mm	250 ft	25 ft
ST-PVC2-0.310-XX-Y	8.0mm → 4.0mm	250 ft	25 ft
ST-PVC2-0.375-XX-Y	9.5mm → 4.8mm	250 ft	25 ft
ST-PVC2-0.500-XX-Y	12.7mm → 6.4mm	250 ft	25 ft
ST-PVC2-0.625-XX-Y	15.9mm → 7.9mm	250 ft	25 ft
ST-PVC2-0.750-XX-Y	19.1mm → 9.5mm	250 ft	25 ft
ST-PVC2-1.000-XX-Y	25.4mm → 12.7mm	250 ft	25 ft
ST-PVC2-1.500-XX-Y	38.1mm → 19.1mm	100 ft	25 ft
ST-PVC2-2.000-XX-Y	63.5mm → 31.8mm	100 ft	25 ft
ST-PVC2-2.500-CL-Y	50.8mm → 25.4mm	100 ft	25 ft
ST-PVC2-3.000-CL-Y	76.2mm → 38.1mm	50 ft	25 ft

For the “XX” value in the part number: specify **BK** for Black; **CL** for Clear