



InsulShrink™ Viton Heat Shrink Tubing

2:1 shrink ratios - 392°F / 200°C Maximum Operating Temperature



- Good general chemical resistance.
- Available in black only.
- Easily cut to length.
- MIL-I-23053/5
- Shrink temperature 347°F / 175°C

InsulShrink™ Viton® Heat-Shrink Tubing - 2:1 shrink ratio			
Part Number	Shrink Range Normal size → Shrunk	Spool Size & Price	
		Bulk Spool	Shop Spool
ST-VIT2-0.1250-XX-Y	0.125 → 0.041	200 ft / \$ 765.00	25 ft / \$ 108.12
ST-VIT2-0.1875-XX-Y	0.187 → 0.062	200 ft / \$ 805.00	25 ft / \$ 113.12
ST-VIT2-0.2500-XX-Y	0.250 → 0.083	200 ft / \$ 840.00	25 ft / \$ 117.50
ST-VIT2-0.3750-XX-Y	0.375 → 0.125	200 ft / \$ 1005.00	25 ft / \$ 138.12
ST-VIT2-0.5000-XX-Y	0.500 → 0.166	100 ft / \$ 702.50	25 ft / \$ 188.12
ST-VIT2-0.6250-XX-Y	0.625 → 0.166	100 ft / \$ 902.50	25 ft / \$ 238.12
ST-VIT2-0.7500-XX-Y	0.750 → 0.250	100 ft / \$ 1102.50	25 ft / \$ 288.12
ST-VIT2-0.8750-XX-Y	0.875 → 0.250	50 ft / \$ 712.50	25 ft / \$ 368.75
ST-VIT2-1.0000-XX-Y	1.000 → 0.333	50 ft / \$ 802.50	25 ft / \$ 413.75
ST-VIT2-1.2500-XX-Y	1.250 → 0.333	50 ft / \$ 1203.75	25 ft / \$ 614.37
ST-VIT2-1.5000-XX-Y	1.500 → 0.500	50 ft / \$ 1236.25	25 ft / \$ 630.62
ST-VIT2-2.0000-XX-Y	2.000 → 0.666	50 ft / \$ 3375.00	25 ft / \$ 1700.00