

Spiral Wrap – Mine Approved Hard Shell Hose and Cable Protection

MSHA IC-271

SafeEdge™



- SafeEdge™ abrasion protection spiral wrap is manufactured from highly impact resistant high density polyethylene, and is simply wrapped over hose or cable to provide a tough protection shell to reduce abrasion damage.
- Rounded edges prevents hose and cable damage from flexing of spiral. Superior to cheaper spiral made from slit plastic pipe resulting in sharp edges.
- Available in sizes to wrap individual or bundled hoses and cables with a total ID up to 3.9 inches or 99mm.
- Stays in place without sliding. Springs back when twisted and pulled.
- MSHA IC-271 approved. Available only in a dark grey color.
- Temperature range -60 to + 175°F. Resistant to acids, oils and solvents.

SafeEdge™ High Density Polyethylene Hard Shell Spiral Wrap for Cable & Hose Abrasion Protection - MSHA IC-271 Approved					
See notes for available lengths					
Part Number	ID Size			Pitch in inches	Wall Thickness in inches
	inch	mm	-dash		
SW-HDP-MINE-0.50-M016-10-ZZZ	0.50	13	-08	0.8	.05
SW-HDP-MINE-0.63-M016-10-ZZZ	0.63	16	-10	0.8	.05
SW-HDP-MINE-0.81-M021-14-ZZZ	0.81	21	-14	1.0	.10
SW-HDP-MINE-1.06-M027-17-ZZZ	1.06	27	-17	0.9	.10
SW-HDP-MINE-1.36-M035-22-ZZZ	1.36	35	-22	.94	.11
* SW-HDP-MINE-1.70-M043-27-ZZZ	1.70	43	-27	1.2	.13
SW-HDP-MINE-2.20-M056-35-ZZZ	2.20	56	-35	1.5	.15
* SW-HDP-MINE-2.60-M066-42-ZZZ	2.60	66	-42	1.75	.17
SW-HDP-MINE-3.20-M081-51-ZZZ	3.20	81	-51	1.75	.19
SW-HDP-MINE-3.90-M099-62-ZZZ	3.90	99	-62	2.00	.22

* For SW-HDP-MINE-1.70-M043-27-ZZZ and SW-HDP-MINE-2.60-M066-42-ZZZ, use “025”, “050” or “100” for length in feet as the “ZZZ” value in the part number

For all other part numbers, the coil length is 82 feet (use 082 in the part number).

This product is made to order; typical production is 10 to 15 working days.
Some stock lengths may exist - please call