

Woven Fiberglass 7628 MIL-C-20079H Type II Class I Hullboard Lagging Tape 1200°F / 648°C: DeltaGlass™ Very High Temperature & Heat Resistant



- Woven from filament fiberglass yarns (non texturized), this tape will withstand temperatures up to 1200°F / 648°C in continuous service.
- 0.007" / .177 mm thickness.
- Available in 1", 1 ½", 2", 3", 4" and 6" widths.
- Used extensively as a hullboard tape.
- Meets MIL-C-20079H: very low chloride and alkali content.
- Other widths available by custom order.
- Various finishes and treatments available including heat cleaned.
- Roll length 50 yards / 150 feet
- Supplied unfinished. Silane finish available at +30% (full case only).

Very High Temperature & Heat Resistant Woven Fiberglass 7628 Hullboard Tape – MIL-C-20079H Type II Class I			
Part Number	Width in / mm		Rolls / case
	T-FG-HBT7628-1.0-M025-007	1.0	
T-FG-HBT7628-1.5-M038-007	1.5	38	72
T-FG-HBT7628-2.0-M051-007	2.0	51	54
T-FG-HBT7628-3.0-M076-007	3.0	76	36
T-FG-HBT7628-4.0-M102-007	4.0	102	27
T-FG-HBT7628-6.0-M152-007	6.0	152	18