

Tacky-Cloth[™] White Rubber Coated Fiberglass Gasket Seal Tape 550°F / 287°C: Tuff-Flex[™] High Temperature Heat Resistant Tape: *With or Without Wire Insert*



This is a widely used and universal tape for making gaskets, especially where a rough or uneven surface or flange exists. The tape is a fiberglass base with a special white rubber formulation coating. The tape is tacky, and has a plastic film surface covering that is removed before installation. The tape will stick to itself once the film is removed.

Wire Inserted Version: The fill (width wise) yarn for this version of the fabric has a twisted brass wired formed with it, providing additional dimensional stability/strength.

Same price, either version.

Tuff-Flex™ High Temperature White Rubber Coated Fiberglass Universal Gasket Tape (Tacky Cloth)	
Part Number	Width in / mm
T-FG-TC-M013-08-X-Z	.50 / 13
T-FG-TC-M019-12-X-Z	.75 / 19
T-FG-TC-M025-16-X-Z	1.0 / 25
T-FG-TC-M032-20-X-Z	1.25 / 32
T-FG-TC-M038-24-X-Z	1.50 / 38
T-FG-TC-M051-32-X-Z	2.00 / 51
T-FG-TC-M076-48-X-Z	3.00 / 76
T-FG-TC-M102-64-X-Z	4.00 / 102
T-FG-TC-M127-80-X-Z	5.00 / 127

550°F / 287°C continuous rating, excellent sealing properties as a gasket material

0.5" and 0.75" width tapes not available in A or E thickness For the "X" value specify either A, B, C, D, or E

"A" thickness = .062 / 1.6mm; "B" thickness = .125 / 3.2mm; "C" thickness = .187 / 4.8mm; "D" thickness = .250 / 6.3mm; "E" thickness = .375 / 7.9mm

For the "Z" value, use "W" to specify with wire insert and "N" to specify no wire

Curing: It is recommended that this material be cured in situ. This material must be heated to a minimum of 300°F within 60 minutes, then it must sit at 300°F or higher for 90 minutes for the rubber to fully cure. Do not overtorque the material during this curing time or the rubber will be squeezed off of the base material. If the material is not fully cured, the rubber will drip from the material causing voids. After curing the material can be exposed to a lower operational temperature.

