

Fiberglass Woven Thermal Insulating Tape with Hook/Loop Closure InsulTape™ Thermal Insulation and Personnel Burn Protection 1200°F / 648°C: Very High Temperature & Heat Resistant



Manufactured of texturized fiberglass yarns, the fiberglass base tape will withstand temperatures up to 1200°F / 648°C in continuous service.

In service, the hook and loop closure can be used up to 325°F/162°C without failure.

The tape is “closed” to form a sleeve for use on hoses, lines and pipes.

When used on hot metal piping, it proves accidental contact burn protection and can be used to meet the OSHA requirements for burn protection.

Standard hook and loop width is ½”. Other widths available.

Tapes may be joined in order to create larger ID sleeves.

Tapes are sewn at each end to help prevent fray. May be cut to desired length.

The hook and loop is available in 25 colours to help make the pipe/hose they cover easily identifiable.

Very High Temperature & Heat Resistant Fiberglass Woven Tape with Hook/Loop Closure 1/8” / 0.125” / 3.2mm thickness			
Part Number	Tape Width in / mm		ID Inch
T-FG-WVC-2.500-M064-X	2.5	64	0.58” / -09
T-FG-WVC-3.000-M076-X	3.0	76	0.75” / -12
T-FG-WVC-3.500-M089-X	3.5	89	0.90” / -14
T-FG-WVC-4.000-M102-X	4.0	102	1.06” / -17
T-FG-WVC-4.500-M114-X	4.5	114	1.22” / -20
T-FG-WVC-5.000-M127-X	5.0	127	1.39” / -22
T-FG-WVC-5.500-M140-X	5.5	140	1.55” / -25
T-FG-WVC-6.000-M152-X	6.0	152	1.70” / -27

For “X” specify hook and loop color – if not specified black will be used

- This tape is 1/8” / .125” / 3.2mm thick
- Add “-HT” to the part number for heat treated version. Add \$6.00 to roll price for heat treating.
- All tapes are 100 foot / 30 metre lengths.